

Permatex Form-A-Gasket No. 2 Sealant 11oz. Tube

ITW AAMTech

Chemwatch Hazard Alert Code: **2**

Chemwatch: **5058-56**

Issue Date: **10/10/2014**

Version No: **11.1.1.1**

Print Date: **28/10/2014**

Safety Data Sheet according to WHS and ADG requirements

Initial Date: **Not Available**

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Permatex Form-A-Gasket No. 2 Sealant 11oz. Tube
Chemical Name	Not Applicable
Synonyms	PX80011 Permatex Form-A-Gasket No. 2 Sealant 11oz. Tube, PX80015 Permatex Form-A-Gasket No. 2 Sealant 1.5oz. Tube, PX80016 Permatex Form-A-Gasket No. 2 Sealant 3oz. Tube
Proper shipping name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Used to coat industrial or automotive gaskets to improve sealing ability on various engineering components; seal pipe threads.
---------------------------------	--

Details of the manufacturer/importer

Registered company name	ITW AAMTech
Address	100 Hassall Street 2164 NSW Australia
Telephone	1800 177 989
Fax	1800 308 556
Website	www.aamtech.com.au
Email	info@aamtech.com.au

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	1800 039 008
Other emergency telephone numbers	+61 3 9573 3112

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
GHS Classification ^[1]	Skin Sensitizer Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

Permatex Form-A-Gasket No. 2 Sealant 11oz.

GHS label elements



SIGNAL WORD

WARNING

Hazard statement(s)

H317	May cause an allergic skin reaction
------	-------------------------------------

Precautionary statement(s): Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s): Response

P302+P352	IF ON SKIN: Wash with plenty of water and soap
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s): Storage

Not Applicable

Precautionary statement(s): Disposal

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1332-58-7	50-60	kaolin
68187-84-8	15-25	blown castor oil
8050-09-7	10-20	rosin-colophony
64-17-5	<10	ethanol
67-63-0	<2	isopropanol
14808-60-7	0.1-1	silica crystalline - quartz
13463-67-7	0.1-1	titanium dioxide
67-56-1	0.1-1	methanol

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket

Continued...

Permatex Form-A-Gasket No. 2 Sealant 11oz.

	<ul style="list-style-type: none"> ▶ mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	<ul style="list-style-type: none"> ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

	<ul style="list-style-type: none"> ▶ Foam. ▶ Dry chemical powder. ▶ BCF (where regulations permit). ▶ Carbon dioxide.
--	---

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment.
Major Spills	<p>Moderate hazard.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves.
	<p>Personal Protective Equipment advice is contained in Section 8 of the MSDS.</p>

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ DO NOT allow clothing wet with material to stay in contact with skin <p>Remove all ignition sources.</p> <ul style="list-style-type: none"> ▶ Limit all unnecessary personal contact. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area.
Other information	<ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources. ▶ Store in a cool, dry, well-ventilated area.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Metal can or drum
---------------------------	---

Continued...

Permatex Form-A-Gasket No. 2 Sealant 11oz.

	<ul style="list-style-type: none"> ► Packaging as recommended by manufacturer. ► Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<ul style="list-style-type: none"> ► Avoid reaction with oxidising agents

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA


Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	kaolin	Kaolin (a)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	ethanol	Ethyl alcohol	1880 mg/m3 / 1000 ppm	Not Available	Not Available	Not Available
Australia Exposure Standards	isopropanol	Isopropyl alcohol	983 mg/m3 / 400 ppm	1230 mg/m3 / 500 ppm	Not Available	Not Available
Australia Exposure Standards	silica crystalline - quartz	Silica - Crystalline Quartz (respirable dust) / Quartz (respirable dust)	0.1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	titanium dioxide	Titanium dioxide (a)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	methanol	Methyl alcohol	262 mg/m3 / 200 ppm	328 mg/m3 / 250 ppm	Not Available	Sk

EMERGENCY LIMITS

Ingredient	TEEL-0	TEEL-1	TEEL-2	TEEL-3
Permatex Form-A-Gasket No. 2 Sealant 11oz. Tube	Not Available	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
kaolin	Not Available	Not Available
blown castor oil	Not Available	Not Available
rosin-colophony	Not Available	Not Available
ethanol	15,000 ppm	3,300 [LEL] ppm
isopropanol	12,000 ppm	2,000 [LEL] ppm
silica crystalline - quartz	N.E. mg/m3 / N.E. ppm	50 mg/m3
titanium dioxide	N.E. mg/m3 / N.E. ppm	5,000 mg/m3
methanol	25,000 ppm	6,000 ppm

Exposure controls

Appropriate engineering controls	General exhaust is adequate under normal operating conditions.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ► Safety glasses with side shields. ► Chemical goggles. ► Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ► Wear chemical protective gloves, e.g. PVC. ► Wear safety footwear or safety gumboots, e.g. Rubber <p>NOTE:</p> <ul style="list-style-type: none"> ► The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and

Continued...

Permatex Form-A-Gasket No. 2 Sealant 11oz.

	<ul style="list-style-type: none"> ▶ other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▶ Overalls. ▶ P.V.C. apron. ▶ Barrier cream.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Permatex Form-A-Gasket No. 2 Sealant 11oz. Tube

Material	CPI
BUTYL	C
BUTYL/NEOPRENE	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
TEFLON	C
VITON/NEOPRENE	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS P2	-	AX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AX-AUS / Class 1 P2	-
up to 100 x ES	-	AX-2 P2	AX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Reddish-brown paste with an alcohol odour; slightly miscible with water.		
Physical state	Free-flowing Paste	Relative density (Water = 1)	1.5
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available

Continued...

Permatex Form-A-Gasket No. 2 Sealant 11oz.

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	82	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	7.7 Ether=1	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	11% (VOC - by wt)
Vapour pressure (kPa)	4.4 @20C	Gas group	Not Available
Solubility in water (g/L)	Partly miscible	pH as a solution(1%)	Not Applicable
Vapour density (Air = 1)	2.07	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Acute effects from inhalation of high vapour concentrations may be chest and nasal irritation with coughing, sneezing, headache and even nausea. Inhalation hazard is increased at high temperatures.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health).
Skin Contact	Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.
Eye	Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.
Chronic	Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.

Permatex Form-A-Gasket No. 2 Sealant 11oz. Tube	TOXICITY	IRRITATION
	Not Available	Not Available

Continued...

Permatex Form-A-Gasket No. 2 Sealant 11oz.

kaolin	TOXICITY	IRRITATION
	Not Available	Not Available
blown castor oil	TOXICITY	IRRITATION
		Eye (rabbit): 500 mg
		Skin (rabbit): 100 mg/24h SEVERE
	Not Available	Not Available
rosin-colophony	TOXICITY	IRRITATION
	Not Available	Not Available
ethanol	TOXICITY	IRRITATION
	Inhalation (rat) LC50: 20,000 ppm/10h	Eye (rabbit): 500 mg SEVERE
	Inhalation (rat) LC50: 64000 ppm/4h	Eye (rabbit): 100mg/24hr-moderate
	Oral (rat) LD50: 7060 mg/kg	Skin (rabbit): 20 mg/24hr-moderate
		Skin (rabbit): 400 mg (open)-mild
	Not Available	Not Available
isopropanol	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 12800 mg/kg	Eye (rabbit): 10 mg - moderate
	Inhalation (Mouse) LC50: 53000 mg/m3/4h	Eye (rabbit): 100 mg - SEVERE
	Inhalation (Rat) LC50: 72600 mg/m3/4h	Eye (rabbit): 100mg/24hr-moderate
	Intraperitoneal (Guinea pig) LD50: 2560 mg/kg	Skin (rabbit): 500 mg - mild
	Intraperitoneal (Mouse) LD50: 4477 mg/kg	
	Intraperitoneal (Rabbit) LD50: 667 mg/kg	
	Intraperitoneal (Rat) LD50: 2735 mg/kg	
	Intravenous (Mouse) LD50: 1509 mg/kg	
	Intravenous (Rabbit) LD50: 1184 mg/kg	
	Intravenous (Rat) LD50: 1088 mg/kg	
	Oral (Mouse) LD50: 3600 mg/kg	
	Oral (Rabbit) LD50: 6410 mg/kg	
	Oral (Rat) LD50: 5000 mg/kg	
	Oral (rat) LD50: 5045 mg/kg	
	Not Available	Not Available
silica crystalline - quartz	TOXICITY	IRRITATION
	Not Available	Y
titanium dioxide	TOXICITY	IRRITATION
	Oral (Mouse) LD50: >10000 mg/kg *	Skin (human): 0.3 mg /3D (int)-mild *
	Oral (Rat) LD50: >20000 mg/kg *	

Continued...

Permatex Form-A-Gasket No. 2 Sealant 11oz.

	Not Available	Not Available
methanol	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 15800 mg/kg	Eye (rabbit): 100 mg/24h-moderate
	Inhalation (rat) LC50: 64000 ppm/4h	Eye (rabbit): 40 mg-moderate
	Oral (rat) LD50: 5628 mg/kg	Skin (rabbit): 20 mg/24 h-moderate
	Not Available	Not Available

Not available. Refer to individual constituents.

KAOLIN	<p>No significant acute toxicological data identified in literature search. for bentonite clays:</p> <p>Bentonite (CAS No. 1302-78-9) consists of a group of clays formed by crystallisation of vitreous volcanic ashes that were deposited in water.</p> <p>The expected acute oral toxicity of bentonite in humans is very low (LD50>15 g/kg). However, severe anterior segment inflammation, uveitis and retrocorneal abscess from eye exposure were reported when bentonite had been used as a prophypaste.</p>
BLOWN CASTOR OIL	data for similar material - castor oil Nil available Skin (human): 50 mg/48h mild Some tumorigenic effects have been reported in animal studies [RTECS]
ROSIN-COLOPHONY	<p>The following information refers to contact allergens as a group and may not be specific to this product.</p> <p>Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.</p>
ISOPROPANOL	<p>For isopropanol (IPA):</p> <p>Acute toxicity: Isopropanol has a low order of acute toxicity. It is irritating to the eyes, but not to the skin. Very high vapor concentrations are irritating to the eyes, nose, and throat, and prolonged exposure may produce central nervous system depression and narcosis. Human volunteers reported that exposure to 400 ppm isopropanol vapors for 3 to 5 min.</p>
SILICA CRYSTALLINE - QUARTZ	<p>WARNING: For inhalation exposure <u>ONLY</u>: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS</p> <p>The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 µm) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite. Crystalline silica is also known to cause silicosis, a non-cancerous lung disease. Intermittent exposure produces; focal fibrosis, (pneumoconiosis), cough, dyspnoea, liver tumours.</p>
TITANIUM DIOXIDE	<p>The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis.</p> <p>* IUCLID</p>
ETHANOL, METHANOL	<p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p>

Acute Toxicity	⊘	Carcinogenicity	⊘
Skin Irritation/Corrosion	⊘	Reproductivity	⊘
Serious Eye Damage/Irritation	⊘	STOT - Single Exposure	⊘
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	⊘
Mutagenicity	⊘	Aspiration Hazard	⊘

Legend: ✓ – Data required to make classification available

✗ – Data available but does not fill the criteria for classification

Continued...

Permatex Form-A-Gasket No. 2 Sealant 11oz.

– Data Not Available to make classification

CMR STATUS

SKIN	methanol	Australia Exposure Standards - Skin	Sk
------	----------	-------------------------------------	----

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
rosin-colophony	LOW	LOW
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
isopropanol	LOW (Half-life = 14 days)	LOW (Half-life = 3 days)
titanium dioxide	LOW	LOW
methanol	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
rosin-colophony	LOW (BCF = 56.23)
ethanol	LOW (BCF = 3.162)
isopropanol	LOW (BCF = 3.162)
titanium dioxide	LOW (BCF = 10)
methanol	LOW (BCF = 3.162)

Mobility in soil

Ingredient	Mobility
rosin-colophony	LOW (KOC = 21990)
ethanol	HIGH (KOC = 1)
isopropanol	HIGH (KOC = 1.06)
titanium dioxide	LOW (KOC = 23.74)
methanol	HIGH (KOC = 1)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Authority for disposal. Bury or incinerate residue at an approved site. Recycle containers if possible, or dispose of in an authorised landfill.
------------------------------	---

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid	rosin-colophony	Y

Continued...

Permatex Form-A-Gasket No. 2 Sealant 11oz.

Substances Carried in Bulk		
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	titanium dioxide	Z
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	methanol	Y

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

kaolin(1332-58-7) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs"
blown castor oil(68187-84-8) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)"
rosin-colophony(8050-09-7) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
ethanol(64-17-5) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"
isopropanol(67-63-0) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Hazardous Substances Information System - Consolidated Lists"
silica crystalline - quartz(14808-60-7) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Hazardous Substances Information System - Consolidated Lists"
titanium dioxide(13463-67-7) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs"
methanol(67-56-1) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.