

# RAIN-X ORIGINAL GLASS TREATMENT WIPE

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 24-May-2013  
9317SP

CHEMWATCH 4870-93  
Version No:2.1.1.1  
CD 2013/2 Page 1 of 8

---

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

---

### PRODUCT NAME

RAIN-X ORIGINAL GLASS TREATMENT WIPE

### SYNONYMS

"800002244, 25ea"

### PROPER SHIPPING NAME

SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(contains ethanol)

### PRODUCT USE

Glass treatment.

### SUPPLIER

Company: ITW AAMTech

Address:

100 Hassall Street

Wetherill Park

NSW, 2164

Australia

Telephone: +61 2 9828 0900

Emergency Tel:**1800 039 008 (24 hours)**

Emergency Tel:**+61 3 9573 3112 (24 hours)**

Fax: +61 2 9725 4698

---

## Section 2 - HAZARDS IDENTIFICATION

---

### STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

### RISK

Risk Codes

R11

R36

R65

R66

R67

Risk Phrases

• Highly flammable.

• Irritating to eyes.

• HARMFUL- May cause lung damage if swallowed.

• Repeated exposure may cause skin dryness and cracking.

• Vapours may cause drowsiness and dizziness.

### SAFETY

Safety Codes

S16

S25

S36

S37

S39

S51

S09

S29

S40

S13

S26

Safety Phrases

• Keep away from sources of ignition. No smoking.

• Avoid contact with eyes.

• Wear suitable protective clothing.

• Wear suitable gloves.

• Wear eye/face protection.

• Use only in well ventilated areas.

• Keep container in a well ventilated place.

• Do not empty into drains.

• To clean the floor and all objects contaminated by this material, use water.

• Keep away from food, drink and animal feeding stuffs.

• In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

S46 • If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

S60 • This material and its container must be disposed of as hazardous waste.

continued...

# RAIN-X ORIGINAL GLASS TREATMENT WIPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 24-May-2013

9317SP

CHEMWATCH 4870-93

Version No:2.1.1.1

CD 2013/2 Page 2 of 8

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

NAME	CAS RN	%
Tissue moistened by a mixture of ethanol	64-17-5	30-60
acetone	67-64-1	10-30
isopropanol	67-63-0	10-30
water	7732-18-5	Not Spec

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- Not considered a normal route of entry.
- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

### EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Protheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

### NOTES TO PHYSICIAN

- For acute or short term repeated exposures to ethanol:
- Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
- Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
- Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
- Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water course.

continued...

# RAIN-X ORIGINAL GLASS TREATMENT WIPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 24-May-2013

9317SP

CHEMWATCH 4870-93

Version No:2.1.1.1

CD 2013/2 Page 3 of 8

Section 5 - FIRE FIGHTING MEASURES

## FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
  - Severe fire hazard when exposed to heat, flame and/or oxidisers.
  - Vapour forms an explosive mixture with air.
  - Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
- Combustion products include: carbon dioxide (CO<sub>2</sub>), other pyrolysis products typical of burning organic material.

## FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## HAZCHEM

1Z

## Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

### MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Remove all ignition sources.
- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.

### SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

- Avoid storage with oxidisers.

### STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>
Australia Exposure Standards	Rain- X Original Glass Treatment Wipe (Ethyl alcohol)	1000	1880		

continued...

# RAIN-X ORIGINAL GLASS TREATMENT WIPE

Chemwatch Independent Material Safety Data Sheet  
 Issue Date: 24-May-2013  
 9317SP

CHEMWATCH 4870-93  
 Version No:2.1.1.1  
 CD 2013/2 Page 4 of 8

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>
Australia Exposure Standards	Rain- X Original Glass Treatment Wipe (Acetone)	500	1185	1000	2375
Australia Exposure Standards	Rain- X Original Glass Treatment Wipe (Isopropyl alcohol)	400	983	500	1230

The following materials had no OELs on our records

- water: CAS:7732- 18- 5

### MATERIAL DATA

RAIN-X ORIGINAL GLASS TREATMENT WIPE:

- None assigned. Refer to individual constituents.

#### ETHANOL:

- Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat.

Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

For ethanol:

Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects. Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness.

#### ACETONE:

- Odour Threshold Value: 3.6 ppm (detection), 699 ppm (recognition)

Saturation vapour concentration: 237000 ppm @ 20 C

NOTE: Detector tubes measuring in excess of 40 ppm, are available.

Exposure at or below the recommended TLV-TWA is thought to protect the worker against mild irritation associated with brief exposures and the bioaccumulation, chronic irritation of the respiratory tract and headaches associated with long-term acetone exposures.

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

#### ISOPROPANOL:

- Odour Threshold Value: 3.3 ppm (detection), 7.6 ppm (recognition)

Exposure at or below the recommended isopropanol TLV-TWA and STEL is thought to minimise the potential for inducing narcotic effects or significant irritation of the eyes or upper respiratory tract. It is believed, in the absence of hard evidence, that this limit also provides protection against the development of chronic health effects.

#### WATER:

- No exposure limits set by NOHSC or ACGIH.

continued...

# RAIN-X ORIGINAL GLASS TREATMENT WIPE

Chemwatch Independent Material Safety Data Sheet

Issue Date: 24-May-2013

9317SP

CHEMWATCH 4870-93

Version No:2.1.1.1

CD 2013/2 Page 5 of 8

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### PERSONAL PROTECTION

#### RESPIRATOR

- Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

#### EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

#### HANDS/FEET

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.

#### OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.

#### ENGINEERING CONTROLS

- Use in a well-ventilated area.

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Tissue moistened with a clear colourless highly flammable liquid with an alcohol-like odour; mixes with water.

### PHYSICAL PROPERTIES

Liquid.			
Mixes with water.			
State	Liquid	Molecular Weight	Not Available
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°C)	- 2.78 (Setaflash CC)	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	1.0- 2.5
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.810- 0.812
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	VOC 72.5	Evaporation Rate	Fast

## Section 10 - STABILITY AND REACTIVITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

continued...

# RAIN-X ORIGINAL GLASS TREATMENT WIPE

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 24-May-2013  
9317SP

CHEMWATCH 4870-93  
Version No:2.1.1.1  
CD 2013/2 Page 6 of 8

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

■ Not normally a hazard due to physical form of product.  
Ingestion may result in nausea, abdominal irritation, pain and vomiting.

##### EYE

■ Not normally a hazard due to physical form of product.  
This material can cause eye irritation and damage in some persons.

##### SKIN

■ There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing skin condition. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

##### INHALED

■ Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. The odour of isopropanol may give some warning of exposure, but odour fatigue may occur. Inhalation of isopropanol may produce irritation of the nose and throat with sneezing, sore throat and runny nose.

#### CHRONIC HEALTH EFFECTS

■ Prolonged exposure to ethanol may cause damage to the liver and cause scarring. It may also worsen damage caused by other agents. Large amounts of ethanol taken in pregnancy may result in "foetal alcohol syndrome", characterised by delay in mental and physical development, learning difficulties, behavioural problems and small head size. A small number of people develop allergic reactions to ethanol, which include eye infections, skin swelling, shortness of breath, and itchy rashes with blisters.

#### TOXICITY AND IRRITATION

No data for this material.

#### CARCINOGEN

isopropanol	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3	Not classifiable as to its carcinogenicity to humans
-------------	---	-------	---	--

#### SKIN

ethanol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1	
acetone	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1	
isopropanol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1	

## Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

#### Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
ethanol	LOW	MED	LOW	HIGH
acetone	LOW	HIGH	LOW	HIGH
isopropanol	LOW	MED	LOW	HIGH

continued...

# RAIN-X ORIGINAL GLASS TREATMENT WIPE

Chemwatch Independent Material Safety Data Sheet  
Issue Date: 24-May-2013  
9317SP

CHEMWATCH 4870-93  
Version No:2.1.1.1  
CD 2013/2 Page 7 of 8  
Section 12 - ECOLOGICAL INFORMATION

## Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

## Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE SOLID

**HAZCHEM:**  
1Z (ADG7)

**ADG7:**

Class or Division:	4.1	Subsidiary Risk:	None
UN No.:	3175	Packing Group:	II
Special Provision:	216 274	Limited Quantity:	1 kg
Portable Tanks & Bulk Containers - Instruction:	T3 BK1 BK2	Portable Tanks & Bulk Containers - Special Provision:	TP33
Packagings & IBCs - Packing Instruction:	P002 IBC06	Packagings & IBCs - Special Packing Provision:	PP9 B2

Name and Description: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.  
(contains ethanol)

**Air Transport IATA:**

ICAO/IATA Class:	4.1	ICAO/IATA Subrisk:	None
UN/ID Number:	3175	Packing Group:	II
Special provisions:	A46		

Shipping name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(contains ethanol)

**Maritime Transport IMDG:**

IMDG Class:	4.1	IMDG Subrisk:	None
UN Number:	3175	Packing Group:	II
EMS Number:	F- A, S- I	Special provisions:	216 274
Limited Quantities:	1 kg		

Shipping name: SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S.(contains ethanol)

## Section 15 - REGULATORY INFORMATION

**Indications of Danger:**

F Highly Flammable  
Xn Harmful

POISONS SCHEDULE None

**REGULATIONS**

**Regulations for ingredients**

**ethanol (CAS: 64-17-5) is found on the following regulatory lists;**

"Acros Transport Information", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "FEMA Generally Recognized

continued...

## RAIN-X ORIGINAL GLASS TREATMENT WIPE

### Chemwatch Independent Material Safety Data Sheet

Issue Date: 24-May-2013

9317SP

CHEMWATCH 4870-93

Version No:2.1.1.1

CD 2013/2 Page 8 of 8

### Section 15 - REGULATORY INFORMATION

as Safe (GRAS) Flavoring Substances 23 - Examples of FEMA GRAS Substances with Non-Flavor Functions", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Air Transport Association (IATA) Dangerous Goods Regulations", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Competition (German)", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Particular Sports (French)", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Particular Sports (Korean)", "World Anti-Doping Agency - The 2012 Prohibited List World Anti-Doping Code - Substances Prohibited in Particular Sports"

#### acetone (CAS: 67-64-1) is found on the following regulatory lists;

"Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 2", "Australia Customs (Prohibited Exports) Regulations 1958 - Schedule 9 Precursor substances - Part 2", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Illicit Drug Reagents/Essential Chemicals - Category III", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "FEMA Generally Recognized as Safe (GRAS) Flavoring Substances 23 - Examples of FEMA GRAS Substances with Non-Flavor Functions", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments", "United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II", "United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control (Red List) - Table II"

#### isopropanol (CAS: 67-63-0) is found on the following regulatory lists;

"Acros Transport Information", "Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Quarantine and Inspection Service List of chemical compounds that are accepted solely for use at establishments registered to prepare meat and meat products for the purpose of the Export Control Act 1982", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information"

#### water (CAS: 7732-18-5) is found on the following regulatory lists;

"Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information"

#### No data for Rain-X Original Glass Treatment Wipe (CW: 4870-93)

### Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 24-May-2013

Print Date: 24-May-2013

*This is the end of the MSDS.*