

# Material Safety Data Sheet

Infosafe No™. SEPCM Issue Date: July 2011 ISSUED by SEPTONE CS: 1.6.13  
 Product Name: STAINLESS STEEL CLEANER POLISH

**Not classified as hazardous**

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<b>Product Name</b>	STAINLESS STEEL CLEANER POLISH
<b>Product Code</b>	MPSS250
<b>Company Name</b>	Septone Products Pty Ltd (ABN 50 009 745 537)
<b>Address</b>	44 Aquarium Avenue HEMMANT QLD 4174
<b>Emergency Tel.</b>	Business hours only: 1800 000 945 or New Zealand Poisons Information Centre 0800 764 766
<b>Telephone/Fax Number</b>	Tel: (07) 3390 5044 Fax: (07) 3390 5041
<b>Email</b>	general@septone.com.au (For NZ customers other than in emergencies. Your supplier can be contacted)
<b>Recommended Use</b>	Automotive, marine and industrial metal polish.
<b>Other Information</b>	The information herein is, to the best of our knowledge, correct and complete. It describes the safety requirements for this product and should not be construed as guaranteeing specific properties. Since methods and conditions of application are beyond our control, Septone does not accept liability for any damages resulting from the use of, or reliance on, this information, in inappropriate contexts.

## 2. HAZARDS IDENTIFICATION

<b>Hazard Classification</b>	Not classified as hazardous This product is NOT classified as hazardous due to its viscosity and phase stability at temperatures up to and including 40C. Hence, it does NOT require classification using the risk phrase R65.
<b>Safety Phrase(s)</b>	S2 Keep out of reach of children. S23 Do not breathe gas/fumes/vapour/spray S24 Avoid contact with skin. S45 In case of accident or if you feel unwell seek medical advice immediately S53 Avoid exposure - obtain special instructions before use. S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.
<b>Sensitization of Product</b>	None of the components of this product is considered to be a skin or respiratory sensitiser.
<b>Other Information</b>	The presence of Liquid Hydrocarbons in this product suggests the need for the Risk Phrase R65 (Harmful: May cause lung damage if swallowed) to be included on this MSDS. The severity of symptoms after ingestion of Liquid Hydrocarbons depends on whether it is

aspirated into the lungs, as aspiration can cause serious bronchopneumonia. As this product is a viscous oil-in-water emulsion, the likelihood of aspiration of Liquid Hydrocarbons into the lungs is substantially reduced due to the product's form, viscosity and phase stability at temperatures up to 40C.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<b>Chemical Characterization</b>	Solid				
<b>Ingredients</b>	<b><u>Name</u></b>	<b><u>CAS</u></b>	<b><u>Proportion</u></b>	<b><u>Hazard</u></b>	<b><u>R Phrase</u></b>
	Liquid hydrocarbons	64742-82-1	30-60 %	Xn	R65
	Ingredients determined not to be hazardous	-	10-30 %		
	Aluminium Oxide	1344-28-1	10-30 %		
	Water	7732-18-5	Balance		

### 4. FIRST AID MEASURES

<b>Inhalation</b>	Remove the victim from the source of exposure. If the victim is not breathing, apply artificial resuscitation. For all but the most minor symptoms, seek medical attention.
<b>Ingestion</b>	Do NOT induce vomiting. Give water to drink. Seek medical attention.
<b>Skin</b>	Remove contaminated clothing and launder before re-use. Wash affected skin thoroughly with soap and water.
<b>Eye</b>	Hold the eyes open and flush with water for at least 15 minutes. Seek medical attention.
<b>First Aid Facilities</b>	A safety shower and an eye irrigation facility should be provided. This Material Safety Data Sheet should be provided to the attending medical doctor.
<b>Advice to Doctor</b>	Inhalation: Treat symptomatically. CNS depression, characterised by headache and nausea. Ingestion: Gastrointestinal irritation, nausea, vomiting and cramping. CNS depression, ranging from mild headache to anaesthesia and coma. Pulmonary irritation secondary to exhalation of solvent. Lavage with cuffed tube if large quantity ingested. Aspiration is the main danger. Enforce bed rest and observe carefully. Observe for 24 hours for chemical pneumonitis. Longer term medical surveillance may be necessary. Maintain airways and vital functions. Avoid sympathomimetic amines.

### 5. FIRE FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Firefighters should fight large fires with AFFF foam. For smaller fires, suitable extinguishers are dry chemical, carbon dioxide or foam.
<b>Hazards from Combustion Products</b>	During combustion, this product may produce carbon monoxide and other unidentifiable organic compounds.
<b>Special Protective Equipment for</b>	If this product is involved in a fire, firefighters full protective equipment including and self-contained breathing apparatus.

fire  
fighters

**Specific Hazards** None known.

**Other Information** This product is an oil-in-water emulsion and as such is unlikely to flash or to sustain or feed a fire.

## 6. ACCIDENTAL RELEASE MEASURES

**Spills & Disposal** Personnel involved in cleaning up any spills are to wear oil impervious gloves if prolonged or repeated skin contact is likely. The wearing of safety glasses is recommended. Wear a 3M brand 6983 Automotive Dust Respirator if dust concentrations exceed the recommended levels. Remove all sources of heat or ignition. Do not smoke during the clean-up procedure. Cordon off the spillage area. Isolate the source of the spillage or leak. Contain the spillage using a suitable non-flammable absorbent material such as sand or diatomaceous earth (but not sawdust), and then transfer to sealed plastic containers for disposal. Prevent the spillage from entering the sewerage system or waterways.

## 7. HANDLING AND STORAGE

**Handling and Storage** Store in metal containers in a clean, dry, cool, well ventilated place away from foodstuffs. Keep containers well sealed when not in use.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**National Exposure Standards** NOHSC has not assigned an exposure standard for Liquid Hydrocarbons, but the TLV-TWA of 790 mg/m<sup>3</sup> for White Spirit (which is currently under review by NOHSC) may be used as a guide. Dusts generated while using this product will contain aluminium oxide. The exposure standard (TLV-TWA) set by NOHSC for aluminium oxide (as a substance of inherently low toxicity and free from toxic impurities) is 10 mg/m<sup>3</sup>, measured as inspirable dust (source NOHSC, ACGIH).

**Engineering Controls** Natural ventilation adequate under normal conditions of use. Keep containers closed when not in use.

**Respiratory Protection** Avoid breathing vapours and/or dusts. Select and use respirators in accordance with AS/NZS 1715/1716. When vapour or dust concentrations exceed the exposure standards then the use of the following is recommended: Half facepiece respirator with organic vapour (Type A) and dust/mist (Type P1) filters. Filter capacity and respirator type depends on exposure levels.

**Eye Protection** Avoid contact with the eyes. The wearing of safety glasses is recommended, especially for operators who wear contact lenses.

**Hand Protection** Avoid contact with the skin. If prolonged or repeated skin contact is likely, oil impervious gloves should be worn.

**Hygiene Measures** Always wash skin and clothing after using this product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Form** Solid

<b>Appearance</b>	White paste, slight solvent odour.
<b>Boiling Point</b>	100 - 250°C
<b>Solubility in Water</b>	73% disperses in Water
<b>Specific Gravity</b>	1.100 @ 25°C
<b>pH Value</b>	9.5
<b>Evaporation Rate</b>	As for Water
<b>Volatile Component</b>	60% w/w
<b>Flash Point</b>	This product will not flash and does not support combustion.
<b>Flammability</b>	This product is an oil-in-water emulsion and as such is unlikely to flash or to sustain or feed a fire.

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Considered stable. Store below 30°C.
<b>Conditions to Avoid</b>	None known.
<b>Incompatible Materials</b>	Strong oxidising agents.
<b>Hazardous Polymerization</b>	Will not occur.

## 11. TOXICOLOGICAL INFORMATION

<b>Inhalation</b>	The inhalation of vapours may be harmful at high exposure levels. However, due to the form in which the product is supplied and under normal conditions of storage and use, this product does not present an inhalation hazard. Dusts generated while using this product will contain aluminium oxide. Dusts will normally only be generated when shaking the dried polish from polishing pads or cloths.
<b>Ingestion</b>	Moderate irritant. Upon aspiration into the lungs, chemical pneumonitis may develop. Dusts generated while using this product may be regarded as essentially non-irritating if swallowed.
<b>Skin</b>	Mildly irritating to the skin. Signs of irritation include redness, itchiness and eventually cracking of the skin. Irritation usually only occurs after prolonged, repeated skin contact and is due to the de-fatting effect on the skin of the liquid hydrocarbons and to the abrasive action on the skin of the aluminium oxide. May lead to the onset of dermatitis. Dusts generated while using this product will contain aluminium oxide, which is a mild abrasive and which may lead to temporary skin irritation.
<b>Eye</b>	Irritating to the eyes. Signs of irritation include redness, soreness and tear production. Dusts generated while using this product will contain aluminium oxide, which is a mild abrasive and which may lead to scratching of the cornea and temporary irritation.
<b>Chronic Effects</b>	Dermatitis may occur after prolonged, repeated skin contact and is due to the de-fatting effect on the skin of the liquid hydrocarbons and to the abrasive action on the skin of the

aluminium oxide. Compliance with the exposure standard for inspirable dusts should prevent impairment of respiratory function even over many years of exposure.

<b>Reproductive Toxicity</b>	None of the components of this product is considered to be toxic to the unborn foetus.
<b>Mutagenicity</b>	None of the components of this product is considered to be a mutagen.
<b>Carcinogenicity</b>	None of the components of this product is considered to be a carcinogen.

## 12. ECOLOGICAL INFORMATION

<b>Short Summary of Assessment of Environmental Impact</b>	Information on the emulsifiers contained in this product indicates that this product would be classified as biodegradable and would have a low acute toxicity to marine life. Alumina and quartz are not damaging to the aquatic environment.
<b>Other Precautions</b>	Do not smoke whilst using this product.

## 13. DISPOSAL CONSIDERATIONS

<b>Product Disposal</b>	Dispose of large amounts in a suitable chemical dump (check the local statutory requirements).
<b>Container Disposal</b>	Empty containers may be rinsed clean with water then recycled.

## 14. TRANSPORT INFORMATION

<b>Transport Information</b>	This product is classified as non dangerous according to the ACTDG.
<b>IMO Marine Pollutant</b>	This product is not classified by IMO as a Marine Pollutant.

## 15. REGULATORY INFORMATION

<b>Poisons Schedule</b>	Not Scheduled
<b>Packaging &amp; Labelling</b>	This product is not classified as a Schedule 5 Poison because it is a semi-solid preparation.
<b>AICS (Australia)</b>	To the manufacturer's best knowledge, all components of this product are listed on AICS.

## 16. OTHER INFORMATION

<b>Contact Person/Point</b>	Technical Manager (07) 3390 5044
<b>Other Information</b>	Keep container sealed when not in use.

**...End Of MSDS...**

(C) Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.