Septone Superior Cut Liquid Compound

ITW AAMTech

Chemwatch: **22-0934** Version No: **2.1.1.1**

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 1

Issue Date: 27/05/2014 Print Date: 29/05/2014 Initial Date: Not Available S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier	
Product name	Septone Superior Cut Liquid Compound
Chemical Name	Not Applicable
Synonyms	Product Code: ACLC1
Proper shipping name	Not Applicable
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet

Registered company name	ITW AAMTech		
Address	100 Hassall Street Wetherill Park 2164 NSW Australia		
Telephone	+61 2 9828 0900		
Fax	+61 2 9725 4698	I I	1 1 1
Website	Not Available		
Email	general@septone.com.au	i i	1

Emergency telephone number

Association / Organisation	Not Available	I !	
Emergency telephone numbers	1800 039 008 (24 hours)		
Other emergency telephone numbers	+61 3 9573 3112 (24 hours)	1	

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
GHS Classification	Not Applicable
Label elements	
GHS label elements	Not Applicable
SIGNAL WORD	NOT APPLICABLE

Hazard statement(s)

Not Applicable

Precautionary statement(s): Prevention

Not Applicable

Precautionary statement(s): Response

Not Applicable

Precautionary statement(s): Storage

Not Applicable

Precautionary statement(s): Disposal

Not Applicable

Page 2 of 7
Septone Superior Cut Liquid Compound

Issue Date: **27/05/2014**Print Date: **29/05/2014**

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name		
1344-28-1.	30-60	<u>aluminium oxide</u>		
14808-60-7	10-30	silica crystalline - quartz		
64742-47-8	10-30	distillates, petroleum, light, hydrotreated		
Not Available	0-10	ingredients non-hazardous		
7732-18-5	30-60	<u>water</u>		

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: • Wash out immediately with fresh running water. • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. • Seek medical attention without delay; if pain persists or recurs seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ► Immediately remove all contaminated clothing, including footwear. ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

- ▶ foam.
- dry chemical powder.
- carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Fighting

Fire Incompatibility	None known.

Advice for firefighters

Alert Fire Brigade and tell the	m location and nature of hazard

- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
 - ▶ **DO NOT** approach containers suspected to be hot.
 - ▶ Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.

▶ The material is not readily combustible under normal conditions.

- However, it will break down under fire conditions and the organic component may burn.
- Not considered to be a significant fire risk.

 Heat may cause expansion or decomposition.
 - Heat may cause expansion or decomposition with violent rupture of containers.
 - ▶ Decomposes on heating and may produce toxic fumes of carbon monoxide (CO).
 - May emit acrid smoke.

Chemwatch: 22-0934 Page 3 of 7 Version No: 2.1.1.1

Septone Superior Cut Liquid Compound

Issue Date: 27/05/2014 Print Date: 29/05/2014

Combustion products include:

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

	Slippery when spilt.
	Clean up all spills immediately.
	 Avoid breathing vapours and contact with skin and eyes.
Minor Spills	 Control personal contact with the substance, by using protective equipment.
	 Contain and absorb spill with sand, earth, inert material or vermiculite.
	▶ Wipe up.

▶ Place in a suitable, labelled container for waste disposal.

Major Spills

Slippery when spilt. Minor hazard. ▶ Clear area of personnel.

▶ Alert Fire Brigade and tell them location and nature of hazard.

▶ Control personal contact with the substance, by using protective equipment as required.

Prevent spillage from entering drains or water ways.

▶ Contain spill with sand, earth or vermiculite.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	 Limit all unnecessary personal contact. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. When handling DO NOT eat, drink or smoke. Always wash hands with soap and water after handling. Avoid physical damage to containers. Use good occupational work practice.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this MSDS. Store below 30 deg.

Conditions for safe storage, including any incompatibilities

Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Avoid storage with oxidisers

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

INOTEDIENT DAIA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	aluminium oxide	Aluminium oxide	10 (mg/m3)	Not Available	Not Available	This value is for inspirable dust containing no asbestos and < 1% crystalline silica (see Chapter 14)
Australia Exposure Standards	silica crystalline - quartz	Quartz (respirable dust) / Silica - Crystalline Quartz (respirable dust)	0.1 (mg/m3)	Not Available	Not Available	(see Silica - Crystalline) / (see Chapter 14)
Australia Exposure Standards	distillates, petroleum, light, hydrotreated	Oil mist, refined mineral	5 (mg/m3)	Not Available	Not Available	Not Available

Version No: 2.1.1.1

Septone Superior Cut Liquid Compound

Issue Date: **27/05/2014**Print Date: **29/05/2014**

Ingredient	TEEL-0	TEEL-1	TEEL-2	TEEL-3
aluminium oxide	15(ppm)	15(ppm)	15(ppm)	25(ppm)
silica crystalline - quartz	0.3(ppm)	0.3(ppm)	0.3(ppm)	50(ppm)
water	500(ppm)	500(ppm)	500(ppm)	500(ppm)

Ingredient	Original IDLH	Revised IDLH
silica crystalline - quartz	N.E.(mgm3)N.E.(ppm)	50(mgm3)

Exposure controls

Appropriate engineering controls	General exhaust is adequate under normal operating conditions.
Personal protection	
Eye and face protection	Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	▶ Overalls.▶ Eyewash unit.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the $\it computer-generated$ selection:

Septone Superior Cut Liquid Compound

Material	СРІ
BUTYL	A
NEOPRENE	Α
VITON	Α

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Slightly gritty off-white viscous liquid with pineapple / coconut odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available

Chemwatch: **22-0934**Version No: **2.1.1.1**

Septone Superior Cut Liquid Compound

Issue Date: 27/05/2014 Print Date: 29/05/2014

pH (as supplied)	9.2	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100-250	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	As for water	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	48 w/w
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution(1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Acute effects from inhalation of high vapour concentrations may be chest and nasal irritation with coughing, sneezing, headache and even nausea.
Ingestion	Ingestion may result in nausea, abdominal irritation, pain and vomiting
Skin Contact	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. The material may accentuate any pre-existing dermatitis condition
Eye	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
Chronic	Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following. Long term inhalation of dusts containing crystalline silicas may lead to silicosis. Effects are cumulative, with nodular fibrosis, respiratory impairment, emphysema, even restriction, obstruction of lung function in severe cases. Chronic symptoms produced by crystalline silicas included decreased vital lung capacity and chest infections. Lengthy exposure may cause silicosis, a disabling form of pneumoconiosis which may lead to fibrosis, a scarring of the lining of the air sacs in the lung. Symptoms may appear 8 to 18 months after initial exposure. Smoking increases this risk. [Dusts may be generated when cleaning the dried product from compounding pads or cloths. These dusts will contain encapsulated crystalline silica in the form of quartz.

Septone Superior Cut Liquid	TOXICITY	IRRITATION
Septone Superior Cut Liquid Compound	Not Available	Not Available
aluminium oxide	TOXICITY	IRRITATION
aluminum Oxide	Not Available	Not Available
	TOXICITY	IRRITATION
silica crystalline - quartz		Υ
	Not Available	Not Available
distillator metualorum limbt broducturated	TOXICITY	IRRITATION
distillates, petroleum, light, hydrotreated	Not Available	Not Available
·	TOXICITY	IRRITATION
water	Not Available	Not Available

Not available. Refer to individual constituents.

SILICA CRYSTALLINE - QUARTZ

 $\textbf{WARNING:} \ \, \text{For inhalation exposure} \ \, \underline{\text{ONLY:}} \ \, \text{This substance has been classified by the IARC as Group 1:} \ \, \textbf{CARCINOGENIC TO HUMANS}$

Septone Superior Cut Liquid Compound

Issue Date: 27/05/2014 Print Date: 29/05/2014

0

Aspiration Hazard

The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 um) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite. Crystalline silica is also known to cause silicosis, a non-cancerous lung disease. Intermittent exposure produces; focal fibrosis, (pneumoconiosis), cough, dyspnoea, liver tumours. * Millions of particles per cubic foot (based on impinger samples counted by light field techniques). NOTE: the physical nature of quartz in the product determines whether it is likely to present a chronic health problem. To be a hazard the material must enter the breathing zone as respirable particles. For "kerosenes" Acute toxicity: Oral LD50s for three kerosenes (Jet A, CAS No. 8008-20-6 and CAS No. 64742-81-0) ranged from > 2 to >20 g/kg The dermal LD50s of the same three kerosenes were all >2.0 g//kg. Inhalation LC50 values in Sprague-Dawley rats for straight run kerosene (CAS No. 8008-20-6) and hydrodesulfurised kerosene (CAS No. 64742-81-0) were reported to be > 5 and > 5.2 mg/l, respectively. No DISTILLATES, PETROLEUM, LIGHT, mortalities in rats were reported in rats when exposed for eight hours to saturated vapor of deodorised kerosene (probably a desulfurised HYDROTREATED kerosene). Six hour exposures of cats to the same material produced an LC50 of >6.4 mg/l When tested in rabbits for skin irritation, straight run kerosene (CAS No. 8008-20-6) produced "moderate" to "severe" irritation. Six additional skin irritation studies on a range of kerosenes produced "mild" to "severe" irritation. An eye irritation in rabbits of straight run kerosene (CAS No. 8008-20-6) produced Draize scores of 0.7 and 2.0 (unwashed and washed eyes) at 1 hour. By 24 hours, the Draize scores had returned to zero. **ALUMINIUM OXIDE, WATER** No significant acute toxicological data identified in literature search. **Acute Toxicity** Carcinogenicity 0 0 Skin Irritation/Corrosion 0 Reproductivity 0 STOT - Single Exposure 0 Serious Eye Damage/Irritation 0 Respiratory or Skin sensitisation 0 STOT - Repeated Exposure

CMR STATUS

Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

Mutagenicity

0

Toxicity

DO NOT discharge into sewer or waterways

[Information on the emulsifiers contained in this product indicates that this product would be classified as biodegradable and would have a low acute toxicity to marine life. The hydrocarbon contained in this product is biodegradable. It degrades rapidly in air by photo-chemical means. Alumina and quartz are not damaging to the aquatic environment. Avoid product dispersion in the environment.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Not Available	Not Available	Not Available

Bioaccumulative potential

Ingredient	Bioaccumulation
Not Available	Not Available

Mobility in soil

Ingredient	Mobility
Not Available	Not Available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Labels Required		
	Marine Pollutant	NO
	HAZCHEM	Not Applicable

Land transport (): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Septone Superior Cut Liquid Compound

Issue Date: 27/05/2014
Print Date: 29/05/2014

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

aluminium oxide(1344-28-1.) is found on the following regulatory lists

"International Council of Chemical Associations (ICCA) - High Production Volume List", "Australia Exposure Standards", "FisherTransport Information", "OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)", "Sigma-AldrichTransport Information", "Australia High Volume Industrial Chemical List (HVICL)", "Acros Transport Information"

silica crystalline - quartz(14808-60-7) is found on the following regulatory lists

"Australia Hazardous Substances Requiring Health Surveillance", "Australia - Northern Territories Work Health and Safety National Uniform Legislation Regulations- Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring","Australia Western Australia Hazardous Substances Requiring Health Surveillance", "Australia Exposure Standards", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Restricted hazardous chemicals", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments" "Fisher Transport Information", "Australia - Tasmania Hazardous Substances Prohibited for Specified Uses"."Australia - Northern Territories Work Health and Safety National Uniform Legislation Regulations- Restricted hazardous chemicals", "Australia - Tasmania Hazardous Substances Requiring Health Surveillance", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "OECD List of High Production Volume (HPV) Chemicals","Australia - Western Australia Hazardous Substances Prohibited for Specified Uses or Methods of Handling","Australia - South Australia - Work Health and Safety Regulations 2012 - Restricted hazardous chemicals", "Australia - Queensland Work Health and Safety Regulation - Restricted hazardous chemicals", "Australia Inventory of Chemical Substances (AICS)", "Australia - Queensland Work Health and Safety Regulation - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - South Australia - Work Health and Safety Regulations 2012 - Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring","Australia Occupational Health and Safety (Commonwealth Employment) (National Standards) Regulations 1994 - Hazardous Substances Requiring Health Surveillance", "OECD Existing Chemicals Database", "Sigma-AldrichTransport Information", "Australia - New South Wales - Work Health and Safety Regulation 2011 Restricted hazardous chemicals", "Australia Work Health and Safety Regulations 2011 - Hazardous chemicals (other than lead) requiring health monitoring", "Australia High Volume Industrial Chemical List (HVICL)", "Australia - New South Wales - Work Health and Safety Regulation 2011 - Requirements for health monitoring -Hazardous chemicals (other than lead) requiring health monitoring","Australia - Tasmania - Work Health and Safety Regulations 2012 - Requirements for Health Monitoring - Hazardous chemicals (other than lead) requiring health monitoring","Australia Work Health and Safety Regulations 2011 - Restricted hazardous chemicals","Australia - New South Wales Hazardous Substances Requiring Health Surveillance", "Australia Hazardous Substances Information System -Consolidated Lists","Australia - New South Wales Hazardous Substances Prohibited for Specific Uses","Australia - South Australia Hazardous Substances Requiring Health Surveillance"

distillates, petroleum, light, hydrotreated(64742-47-8) is found on the following regulatory lists

"International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia Exposure Standards", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "OSPAR National List of Candidates for Substitution – Norway", "OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "OECD Existing Chemicals Database", "United Nations Recommendations on the Transport Dangerous Goods Model Regulations (Spanish)", "Sigma-AldrichTransport Information", "Australia High Volume Industrial Chemical List (HVICL)", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "International Fragrance Association (IFRA) Survey: Transparency List"

water(7732-18-5) is found on the following regulatory lists

"WHO Model List of Essential Medicines - Adults", "OSPAR National List of Candidates for Substitution – Norway", "OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)", "Sigma-AldrichTransport Information", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "Australia High Volume Industrial Chemical List (HVICL)", "International Fragrance Association (IFRA) Survey: Transparency List"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.