# **Material Safety Data Sheet**

Infosafe No<sup>TM</sup>. SEPAP Issue Date: November 2012 ISSUED by SEPTONE CS: 1.6.13

Product Name: AEROSOL BRAKE CALIPER & DRUM PAINT

#### Classified as hazardous

#### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name AEROSOL BRAKE CALIPER & DRUM PAINT

Company Name Septone Products Pty Ltd (ABN 50 009 745 537)

Address 44 Aquarium Avenue HEMMANT

QLD 4174

Emergency Tel. Business hours only: 1800 000 945 or New Zealand Poisons

Information Centre 0800 764 766

Telephone/Fax Number Tel: (07) 3390 5044 Fax: (07) 3390 5041

Email general@septone.com.au (For NZ customers other than in

emergencies. Your supplier can be contacted)

Recommended

Use

Automotive brake caliper and brake drum enamel paint, aerosol

form, available in a range of colours

Other Names Name Mancode

AEROSOL BRAKE CALIPER & DRUM PAINT ALUMINIUM

AEROSOL BRAKE CALIPER &

AACPB400

AACPA400

DRUM PAINT BLUE

AEROSOL BRAKE CALIPER &

DRUM PAINT GLOSS BLACK

AACPGB400

AEROSOL BRAKE CALIPER &

AERUSUL BRAKE CALIPER O

AACPR400

DRUM PAINT RED

AEROSOL BRAKE CALIPER &

DRUM PAINT SATIN BLACK

AACPSB400

AEROSOL BRAKE CALIPER &

AACPY400

AACPHP400

DRUM PAINT YELLOW

AEROSOL BRAKE CALIPER &

DRUM PAINT HOT PINK

## 2. HAZARDS IDENTIFICATION

Hazard Classified as hazardous Classification HAZARDOUS SUBSTANCE.

DANGEROUS GOODS.

Hazard classification according to the criteria of NOHSC. Dangerous goods classification according to the Australia

Dangerous Goods Code.

Risk Phrase(s) Classified as hazardous R11 Highly flammable.

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.

Safety Phrase(s)

S16 Keep away from sources of ignition - No smoking.

S2 Keep out of reach of children.

S25 Avoid contact with eyes.

S29 Do not empty into drains.

S33 Take precautionary measures against static discharges.

 ${
m S45}$  In case of accident or if you feel unwell seek medical

advice immediately

S53 Avoid exposure - obtain special instructions before use.

S9 Keep container in a well ventilated place.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition, information on ingredients

There are no lead or chrome pigments used in the manufacture of this paint.

Chemical

Gas

#### Characterization

Ingredients	<b>Name</b>	<u>CAS</u>	<b>Proportion</b>	<b>Hazard</b>	R Phrase
	Hydrocarbon propellant	68475- 59-2	30-60 %	F+	R12
	Acetone	67-64-1	30-60 %	Xi, F	R11, R36, R66, R67
	Ingredients determined not be be hazardous		10-30 %		
	Xylene	1330-20-7	10-30 %	Xn, Xi	R10, R20/21, R38
	Toluene	108-88-3	10-30 %	Xn, F	R11, R20

#### 4. FIRST AID MEASURES

Inhalation	Rescuers	should	wear	respiratory	protection.	Remove	the	wictim
innaiaiinn	MESCHETS	SHOULU	wear	TESPITATOLY	DIOCECCIOII.	1/61110 A G	CIIC	$\vee \perp \cup \cup \perp \Pi$

from the source of exposure. If the victim is not breathing, apply artificial resuscitation. For all but the most minor  $\frac{1}{2} \left( \frac{1}{2} \right)$ 

symptoms, seek medical attention.

Ingestion If sprayed in mouth, rinse mouth with water. Do NOT induce

vomiting. Give water to drink. Seek medical attention.

**Skin** Remove contaminated clothing and launder before re-use. Wash

affected skin and hair thoroughly with soap and water.

Hold the eyes open and flush with water for at least 15

minutes. Seek medical attention.

First Aid A safety shower and an eye irrigation facility should be

Facilities provided. This Material Safety Data Sheet should be provided to

the attending medical doctor.

Advice to Doctor Inhalation: Treat symptomatically. CNS depression,

characterised by headache and nausea.

Ingestion: Gastrointestinal irritation, nausea, vomiting and cramping. CNS depression, ranging from mild headache to anaesthesia and coma. Pulmonary irritation secondary to exhalation of solvent. Lavage with cuffed tube if large quantity ingested. Aspiration is the main danger. Enforce bed rest and observe carefully. Prophylactic antibiotics are useful. Observe for 24 hours for chemical pneumonitis. Longer term medical surveillance may be necessary. Maintain airways

and vital functions. Avoid sympathomimetic amines.

Other Information

Eye

For advice, contact a Poisons Information Centre (phone Australia 13 1126, New Zealand 0800 764 766) or a doctor at

once.

#### 5. FIRE FIGHTING MEASURES

**Suitable** 

**Extinguishing** Media

Firefighters should fight large fires with AFFF foam. For smaller fires, suitable extinguishers are dry chemical, carbon dioxide or foam.

**Special Protective Equipment for**  If this product is involved in a fire, firefighters should wear full protective equipment including self-contained breathing apparatus.

fire fighters

Specific Hazards Highly flammable. Aerosol containers are highly pressurised and

can explode in a fire. Keep intact containers cool using a

water fog. Vapours are heavier than air.

Other **Information**  Extremely flammable. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - no smoking.

### 6. ACCIDENTAL RELEASE MEASURES

# Spills & **Disposal**

Personnel involved in cleaning up any spills are to wear appropriate protective equipment. Remove all sources of heat or ignition. Do not smoke during the clean-up procedure. Cordon off the spillage area. Isolate the source of the spillage or leak. Contain the spillage using a suitable non-flammable absorbent material such as sand or diatomaceous earth (but not sawdust), and then transfer to sealed metal containers for disposal. Prevent the spillage from entering the sewerage system or waterways. Do not puncture or incinerate aerosol cans, even when empty.

#### 7. HANDLING AND STORAGE

# Handling and **Storage**

Pressurised dispenser. Highly flammable. Do not pierce or burn, even when empty. Do not spray on or near a naked flame, any incandescent material or hot surface. Keep away from all sources of heat or ignition, including sparks and naked flames - no smoking. Use only in a well ventilated area. Protect from sunlight and do not expose to temperatures above 50°C. Store in acccordance with local regulations in a cool, well ventilated place away from sources of heat or ignition. Keep out of the reach of children and away from strong oxidising materials. Store in accordance with local regulations as this product is defined under ACTDG to be dangerous goods.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards	<u>Name</u>	mg/m3 (STEL)	ppm (STEL)	mg/m3 (TWA)		TWA Footnote		
	Acetone	2375	1000	1185	500			
	Xylene	655	150	350	80			
	Toluene	565	150	377	100			
Engineering Controls	Ensure that the ventilation is adequate to maintain air concentrations below the exposure standards. If necessary, provide local exhaust ventilation. Ventilation equipment must be explosion proof. Isolate from all sources of heat or ignition, including sparks and naked flames.							
Personal Protective Equipment	Avoid contact with the skin and eyes and avoid breathing the vapour or spray mists. If prolonged or repeated skin contact is likely, oil impervious gloves should be worn. Wear safety glasses if spray mists are produced during use. Wear an organic							

vapour resistant respirator meeting the requirements of AS 1716 if vapour or spray mist concentrations exceed the exposure standards. Always wash skin and clothing after using this product.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form

**Appearance** 

Coloured paint, solvent odour (in aerosol form).

**Boiling Point** 

-42°C minimum

Solubility in

Immiscible

Water

Specific Gravity 0.76 approximately

-150°C (propellant)

**Flash Point Flammability** 

Highly flammable.

**Flammable** 

Not known

Limits -

Lower

**Flammable** 

Not known

Limits -Upper

#### 10. STABILITY AND REACTIVITY

Chemical

Considered stable to heat and light. Store below 30°C.

**Stability** 

**Conditions to** 

Avoid

Sources of heat or ignition, including sparks and naked flames. Static electricity discharges. An explosive air-vapour mix may form - ensure adequate ventilation. Vapours are heavier than

air.

**Incompatible** 

**Materials** 

Strong oxidising agents.

Hazardous **Decomposition** 

**Products** 

Hazardous

During combustion, this product may produce carbon monoxide and other unidentifiable organic compounds.

Will not occur.

**Polymerization** 

#### 11. TOXICOLOGICAL INFORMATION

Inhalation

Intentional misuse by deliberately concentrating and inhaling

the contents of aerosols can be harmful or fatal.

This product contains a hydrocarbon propellant which includes

propane and butane. Propane is regarded by NOHSC as an

asphyxiant (Refer NOHSC:3008(1991).

May be harmful at high exposure levels. May irritate the nose and respiratory tract. Prolonged irritation may cause headaches

and nausea.

Ingestion

Harmful. Upon aspiration into the lungs, chemical pneumonitis

may develop.

Skin

Mildly irritating to the skin. Signs of irritation include redness, itchiness and eventually cracking of the skin.

Irritation usually only occurs after prolonged, repeated skin contact and is due to the de-fatting effect on the skin of the

solvents. May lead to the onset of dermatitis.

Eye

Irritating to the eyes. Signs of irritation include redness,

soreness and tear production.

Chronic Effects Skin irritation may occur after prolonged, repeated skin

contact and is due to the de-fatting effect on the skin of the

solvents. May lead to the onset of dermatitis.

Reproductive

**Toxicity** 

None of the components of this product is considered to be

toxic to the unborn foetus.

None of the components of this product is considered to be a **Mutagenicity** 

mutagen.

None of the components of this product is considered to be a Carcinogenicity

carcinogen.

#### 12. ECOLOGICAL INFORMATION

Avoid release of contents into the environment. **Ecological** 

atmospheric conditions.

**Information** 

This product does not contain CFCs.

**Short Summary** 

of

The propellant will vapourise rapidly when released into the atmosphere. The propellant will photochemically decompose under

Assessment of **Environmental** 

**Impact** 

13. DISPOSAL CONSIDERATIONS

Dispose of large amounts in a suitable chemical dump (check the Waste Disposal

local statutory requirements). Do not empty aerosol cans into

drains or release into the environment.

**Container Disposal** 

Empty aerosol cans are recyclable. Dispose of empty aerosol cans by leaving at an appropriate metal recycling collection

point.

14. TRANSPORT INFORMATION

This product is classified as UN 1950, Aerosols. Dangerous **Transport** 

Goods Class 2.1, Packaging Group II. Transport according to the **Information** 

ACTDG.

1950 U.N. Number

Proper Shipping AEROSOLS

Name

2.1 **DG Class** 2D1 **EPG Number** 49

**IERG Number** 

None of the components of this product is classified as a **IMO Marine** 

Marine Pollutant. **Pollutant** 

15. REGULATORY INFORMATION

Not Scheduled **Poisons** 

**Schedule** 

Harmful, Irritant, Highly Flammable Hazard

Category

To the manufacturer's best knowledge, all of the components of **AICS** 

this product are listed on AICS. (Australia)

16. OTHER INFORMATION

Technical Manager (07) 3390-5044 Contact

Person/Point

# ...End Of MSDS...

#### (C) Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.