

# Septone Aerosol Primer Surfacers

ITW AAMTech

Chemwatch: 4600-96

Version No: 2.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 12/05/2014

Print Date: 18/05/2014

Initial Date: Not Available

S.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | Septone Aerosol Primer Surfacers               |
| Chemical Name                 | Not Applicable                                 |
| Synonyms                      | Aerosol Acrylic Primers, Product Code: AAPS400 |
| Proper shipping name          | AEROSOLS                                       |
| Chemical formula              | Not Applicable                                 |
| Other means of identification | Not Available                                  |
| CAS number                    | Not Applicable                                 |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | Application is by spray atomisation from a hand held aerosol pack<br>, Primer for use under automotive acrylic topcoats., There are no lead or chrome pigments used in the manufacture of this paint. |
|--------------------------|---|

### Details of the supplier of the safety data sheet

|                         |  |
|-------------------------|--|
| Registered company name | ITW AAMTech  |
| Address                 | 100 Hassall Street, Wetherill Park 2164<br>NSW Australia |
| Telephone               | +61 2 9828 0900  |
| Fax                     | +61 2 9725 4698  |
| Website                 | general@septone.com.au                                   |
| Email                   | Not Available  |

### Emergency telephone number

|                                   |                            |
|-----------------------------------|----------------------------|
| Association / Organisation        | Not Available              |
| Emergency telephone numbers       | 1800 039 008 (24 hours)    |
| Other emergency telephone numbers | +61 3 9573 3112 (24 hours) |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.**

|                        |   |
|------------------------|---|
| Poisons Schedule       | Not Applicable  |
| GHS Classification [1] | Aerosols Category 1, Acute Toxicity (Inhalation) Category 4, Eye Irrit. 2, Reproductive Toxicity Category 2, STOT - SE (Resp. Irr.) Category 3, STOT - SE (Narcosis) Category 3, STOT - RE Category 2 |
| Legend:                | 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI   |

### Label elements

|                    |   |
|--------------------|---|
| GHS label elements |  |
|--------------------|---|

|             |               |
|-------------|---------------|
| SIGNAL WORD | <b>DANGER</b> |
|-------------|---------------|

### Hazard statement(s)

|      |   |
|------|---|
| H222 | Extremely flammable aerosol                         |
| H332 | Harmful if inhaled                                  |
| H319 | Causes serious eye irritation                       |
| H361 | Suspected of damaging fertility or the unborn child |

## Septone Aerosol Primer Surfer

|        |   |
|--------|---|
| H335   | May cause respiratory irritation                                  |
| H336   | May cause drowsiness or dizziness                                 |
| H373   | May cause damage to organs through prolonged or repeated exposure |
| AUH044 | Risk of explosion if heated under confinement                     |
| AUH066 | Repeated exposure may cause skin dryness and cracking             |

### Precautionary statement(s): Prevention

|      |  |
|------|--|
| P201 | Obtain special instructions before use.  |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source.  |
| P251 | Do not pierce or burn, even after use.   |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray.   |
| P271 | Use only outdoors or in a well-ventilated area.  |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection.                     |

### Precautionary statement(s): Response

|                |  |
|----------------|--|
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312           | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.  |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |

### Precautionary statement(s): Storage

|           |  |
|-----------|--|
| P405      | Store locked up.   |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed.             |

### Precautionary statement(s): Disposal

|      |  |
|------|--|
| P501 | Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration |
|------|--|

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

### Substances

See section below for composition of Mixtures

### Mixtures

| CAS No        | %[weight] | Name                                       |
|---------------|-----------|--|
| 108-88-3      | 10-30     | <a href="#">toluene</a>                    |
| 78-93-3       | 10-30     | <a href="#">methyl ethyl ketone</a>        |
| Not Available | 10-30     | ingredients determined not to be hazardous |
| 1330-20-7     | 0-10      | <a href="#">xylene</a>                     |
| 64-17-5       | 0-10      | <a href="#">ethanol</a>                    |
| 108-10-1      | 0-10      | <a href="#">methyl isobutyl ketone</a>     |
| 123-86-4      | 0-10      | <a href="#">n-butyl acetate</a>            |
| 68476-85-7.   | 10-30     | <a href="#">hydrocarbon propellant</a>     |

## SECTION 4 FIRST AID MEASURES

### Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold the eyelids apart and flush the eye with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |
| <b>Inhalation</b>   | <p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> <li>▶ Remove to fresh air.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> </ul>     |

## Septone Aerosol Primer Surfacer

|                  |   |
|------------------|---|
| <b>Ingestion</b> | <ul style="list-style-type: none"> <li>▶ Transport to hospital, or doctor.</li> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> </ul> |
|------------------|---|

### Indication of any immediate medical attention and special treatment needed

|                        | <p>Treat symptomatically.</p> <p>Following acute or short term repeated exposures to toluene:</p> <ul style="list-style-type: none"> <li>▶ Toluene is absorbed across the alveolar barrier, the blood/air mixture being 11.2/15.6 (at 37 degrees C.) The concentration of toluene, in expired breath, is of the order of 18 ppm following sustained exposure to 100 ppm. The tissue/blood proportion is 1/3 except in adipose where the proportion is 8/10.</li> <li>▶ Metabolism by microsomal mono-oxygenation, results in the production of hippuric acid. This may be detected in the urine in amounts between 0.5 and 2.5 g/24 hr which represents, on average 0.8 gm/gm of creatinine. The biological half-life of hippuric acid is in the order of 1-2 hours.</li> <li>▶ Primary threat to life from ingestion and/or inhalation is respiratory failure.</li> <li>▶ Patients should be quickly evaluated for signs of respiratory distress (eg cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> &lt;50 mm Hg or pCO<sub>2</sub> &gt; 50 mm Hg) should be intubated.</li> <li>▶ Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial damage has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.</li> <li>▶ A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.</li> <li>▶ Epinephrine (adrenaline) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.</li> <li>▶ Lavage is indicated in patients who require decontamination; ensure use.</li> </ul> <p style="text-align: center;">BIOLOGICAL EXPOSURE INDEX - BEI</p> <p>These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Determinant</th> <th>Index</th> <th>Sampling Time</th> <th>Comments</th> </tr> </thead> <tbody> <tr> <td>o-Cresol in urine</td> <td>0.5 mg/L</td> <td>End of shift</td> <td>B</td> </tr> <tr> <td>Hippuric acid in urine</td> <td>1.6 g/g creatinine</td> <td>End of shift</td> <td>B, NS</td> </tr> <tr> <td>Toluene in blood</td> <td>0.05 mg/L</td> <td>Prior to last shift of workweek</td> <td></td> </tr> </tbody> </table> <p>NS: Non-specific determinant; also observed after exposure to other material</p> <p>B: Background levels occur in specimens collected from subjects NOT exposed</p> | Determinant                     | Index    | Sampling Time | Comments | o-Cresol in urine | 0.5 mg/L | End of shift | B | Hippuric acid in urine | 1.6 g/g creatinine | End of shift | B, NS | Toluene in blood | 0.05 mg/L | Prior to last shift of workweek |  |
|------------------------|--|---------------------------------|----------|---------------|----------|-------------------|----------|--------------|---|------------------------|--------------------|--------------|-------|------------------|-----------|---------------------------------|--|
| Determinant            | Index  | Sampling Time                   | Comments |               |          |                   |          |              |   |                        |                    |              |       |                  |           |                                 |  |
| o-Cresol in urine      | 0.5 mg/L   | End of shift                    | B        |               |          |                   |          |              |   |                        |                    |              |       |                  |           |                                 |  |
| Hippuric acid in urine | 1.6 g/g creatinine   | End of shift                    | B, NS    |               |          |                   |          |              |   |                        |                    |              |       |                  |           |                                 |  |
| Toluene in blood       | 0.05 mg/L  | Prior to last shift of workweek |          |               |          |                   |          |              |   |                        |                    |              |       |                  |           |                                 |  |

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

|  |   |
|--|---|
|  | <p><b>SMALL FIRE:</b></p> <ul style="list-style-type: none"> <li>▶ Water spray, dry chemical or CO<sub>2</sub></li> </ul> <p><b>LARGE FIRE:</b></p> <ul style="list-style-type: none"> <li>▶ Water spray or fog.</li> </ul> |
|--|---|

### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

### Advice for firefighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> </ul> |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat or flame.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition with violent container rupture.</li> <li>▶ Aerosol cans may explode on exposure to naked flames.</li> </ul>                                |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

|   |   |
|---|---|
| <b>Minor Spills</b>   | <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Wear protective clothing, impervious gloves and safety glasses.</li> <li>▶ Shut off all possible sources of ignition and increase ventilation.</li> <li>▶ Wipe up.</li> <li>▶ If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.</li> <li>▶ Undamaged cans should be gathered and stowed safely.</li> </ul> |
| <b>Major Spills</b>   | <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> </ul>                            |
| Personal Protective Equipment advice is contained in Section 8 of the MSDS. |   |

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ Avoid contact with incompatible materials.</li> </ul>   |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can</li> <li>▶ Store in original containers in approved flammable liquid storage area.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Keep containers securely sealed. Contents under pressure.</li> <li>▶ Store away from incompatible materials.</li> </ul> |

### Conditions for safe storage, including any incompatibilities

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ Aerosol dispenser.</li> <li>▶ Check that containers are clearly labelled.</li> </ul> |
| <b>Storage incompatibility</b> | Avoid storage with oxidisers  |

### PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

| Source                       | Ingredient             | Material name                 | TWA                                    | STEL                                 | Peak          | Notes         |
|------------------------------|------------------------|-------------------------------|--|--------------------------------------|---------------|---------------|
| Australia Exposure Standards | toluene                | Toluene                       | 191 (mg/m <sup>3</sup> ) / 50 (ppm)    | 574 (mg/m <sup>3</sup> ) / 150 (ppm) | Not Available | Not Available |
| Australia Exposure Standards | methyl ethyl ketone    | Methyl ethyl ketone (MEK)     | 445 (mg/m <sup>3</sup> ) / 150 (ppm)   | 890 (mg/m <sup>3</sup> ) / 300 (ppm) | Not Available | Not Available |
| Australia Exposure Standards | xylene                 | Xylene (o-, m-, p- isomers)   | 350 (mg/m <sup>3</sup> ) / 80 (ppm)    | 655 (mg/m <sup>3</sup> ) / 150 (ppm) | Not Available | Not Available |
| Australia Exposure Standards | ethanol                | Ethyl alcohol                 | 1880 (mg/m <sup>3</sup> ) / 1000 (ppm) | Not Available                        | Not Available | Not Available |
| Australia Exposure Standards | methyl isobutyl ketone | Methyl isobutyl ketone        | 205 (mg/m <sup>3</sup> ) / 50 (ppm)    | 307 (mg/m <sup>3</sup> ) / 75 (ppm)  | Not Available | Not Available |
| Australia Exposure Standards | n-butyl acetate        | n-Butyl acetate               | 713 (mg/m <sup>3</sup> ) / 150 (ppm)   | 950 (mg/m <sup>3</sup> ) / 200 (ppm) | Not Available | Not Available |
| Australia Exposure Standards | hydrocarbon propellant | LPG (liquefied petroleum gas) | 1800 (mg/m <sup>3</sup> ) / 1000 (ppm) | Not Available                        | Not Available | Not Available |

### EMERGENCY LIMITS

| Ingredient          | TEEL-0    | TEEL-1    | TEEL-2    | TEEL-3    |
|---------------------|-----------|-----------|-----------|-----------|
| toluene             | 200(ppm)  | 200(ppm)  | 510(ppm)  | 2900(ppm) |
| methyl ethyl ketone | 200(ppm)  | 200(ppm)  | 2700(ppm) | 4000(ppm) |
| xylene              | 100(ppm)  | 130(ppm)  | 920(ppm)  | 2500(ppm) |
| ethanol             | 1000(ppm) | 3000(ppm) | 3300(ppm) | 3300(ppm) |

## Septone Aerosol Primer Surfacer

|                        |           |           |           |           |
|------------------------|-----------|-----------|-----------|-----------|
| methyl isobutyl ketone | 75(ppm)   | 75(ppm)   | 500(ppm)  | 500(ppm)  |
| n-butyl acetate        | 5(ppm)    | 5(ppm)    | 200(ppm)  | 3000(ppm) |
| hydrocarbon propellant | 1000(ppm) | 2000(ppm) | 2000(ppm) | 2000(ppm) |

| Ingredient             | Original IDLH     | Revised IDLH      |
|------------------------|-------------------|-------------------|
| toluene                | 2,000(ppm)        | 500(ppm)          |
| methyl ethyl ketone    | 3,000(ppm)        | 3,000 [Unch](ppm) |
| xylene                 | 1,000(ppm)        | 900(ppm)          |
| ethanol                | 15,000(ppm)       | 3,300 [LEL](ppm)  |
| methyl isobutyl ketone | 3,000(ppm)        | 500(ppm)          |
| n-butyl acetate        | 10,000(ppm)       | 1,700 [LEL](ppm)  |
| hydrocarbon propellant | 19,000 [LEL](ppm) | 2,000 [LEL](ppm)  |

### Exposure controls

|   |  |
|---|--|
| <b>Appropriate engineering controls</b> | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> |
| <b>Personal protection</b>              |  |
| <b>Eye and face protection</b>          | <p>No special equipment for minor exposure i.e. when handling small quantities.</p> <p><b>OTHERWISE:</b> For potentially moderate or heavy exposures:</p> <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ <b>NOTE:</b> Contact lenses pose a special hazard; soft lenses may absorb irritants and <b>ALL</b> lenses concentrate them.</li> </ul>   |
| <b>Skin protection</b>                  | See Hand protection below  |
| <b>Hand protection</b>                  | <ul style="list-style-type: none"> <li>▶ No special equipment needed when handling small quantities.</li> <li>▶ <b>OTHERWISE:</b></li> <li>▶ For potentially moderate exposures:</li> <li>▶ Wear general protective gloves, eg. light weight rubber gloves.</li> <li>▶ For potentially heavy exposures:</li> <li>▶ Wear chemical protective gloves, eg. PVC. and safety footwear.</li> </ul>   |
| <b>Body protection</b>                  | See Other protection below   |
| <b>Other protection</b>                 | <p>No special equipment needed when handling small quantities.</p> <p><b>OTHERWISE:</b></p> <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eyewash unit.</li> <li>▶ Do not spray on hot surfaces.</li> <li>▶ The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.</li> </ul>  |
| <b>Thermal hazards</b>                  | Not Available  |

### Recommended material(s)

#### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Septone Aerosol Primer Surfacer

| Material           | CPI     |
|--------------------|---------|
| ###n-butyl         | acetate |
| PE/EVAL/PE         | A       |
| BUTYL              | B       |
| ###methyl ethyl    | ketone  |
| ###methyl isobutyl | ketone  |

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as

### Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|------------------------------------|--|----------------------|----------------------|
| up to 10                           | 1000   | AX-AUS / Class1      | -                    |
| up to 50                           | 1000   | -                    | AX-AUS / Class 1     |
| up to 50                           | 5000   | Airline *            | -                    |
| up to 100                          | 5000   | -                    | AX-2                 |
| up to 100                          | 10000  | -                    | AX-3                 |
| 100+                               |  |                      | Airline**            |

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen

"feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|   |   |  |                              |
|---|---|--|------------------------------|
| <b>Appearance</b>                                   | Pale to mid grey highly flammable liquid with a solvent odour; does not mix with water. |  |                              |
| <b>Physical state</b>                               | Liquid  | <b>Relative density (Water = 1)</b>            | 1.14 (excluding propellants) |
| <b>Odour</b>  | Not Available   | <b>Partition coefficient n-octanol / water</b> | Not Available                |
| <b>Odour threshold</b>                              | Not Available   | <b>Auto-ignition temperature (°C)</b>          | Not Available                |
| <b>pH (as supplied)</b>                             | Not Applicable  | <b>Decomposition temperature</b>               | Not Available                |
| <b>Melting point / freezing point (°C)</b>          | Not Available   | <b>Viscosity (cSt)</b>                         | Not Available                |
| <b>Initial boiling point and boiling range (°C)</b> | -42 minimum   | <b>Molecular weight (g/mol)</b>                | Not Available                |
| <b>Flash point (°C)</b>                             | -104 (propellant)   | <b>Taste</b>                                   | Not Available                |
| <b>Evaporation rate</b>                             | Not Available   | <b>Explosive properties</b>                    | Not Available                |
| <b>Flammability</b>                                 | Flammable.  | <b>Oxidising properties</b>                    | Not Available                |
| <b>Upper Explosive Limit (%)</b>                    | Not Available   | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available                |
| <b>Lower Explosive Limit (%)</b>                    | Not Available   | <b>Volatile Component (%vol)</b>               | 87.4 v/w                     |
| <b>Vapour pressure (kPa)</b>                        | Not Available   | <b>Gas group</b>                               | Not Available                |
| <b>Solubility in water (g/L)</b>                    | Immiscible  | <b>pH as a solution(1%)</b>                    | Not Applicable               |
| <b>Vapour density (Air = 1)</b>                     | >1  | <b>VOC g/L</b>                                 | Not Available                |

## SECTION 10 STABILITY AND REACTIVITY

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Elevated temperatures.</li> <li>▶ Presence of open flame.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination<br>If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.<br><b>WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.</b>  |
| <b>Ingestion</b>    | Accidental ingestion of the material may be damaging to the health of the individual.<br>Not normally a hazard due to physical form of product.<br>Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.   |
| <b>Skin Contact</b> | The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either <ul style="list-style-type: none"> <li>▶ produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or</li> <li>▶ produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.</li> </ul> Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. |
| <b>Eye</b>          | Evidence exists, or practical experience predicts, that the material may cause severe eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Eye contact may cause significant inflammation with pain. Corneal injury may occur; permanent impairment of vision may result unless treatment is prompt and adequate. Repeated or prolonged exposure to irritants may cause inflammation characterised by a temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.   |
| <b>Chronic</b>      | Harmful: danger of serious damage to health by prolonged exposure through inhalation.<br><br>Exposure to the material may cause concerns for humans owing to possible developmental toxic effects, generally on the basis that results in appropriate animal studies provide strong suspicion of developmental toxicity in the absence of signs of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not a secondary non-specific consequence of other toxic effects.<br>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.   |

## Septone Aerosol Primer Surfacer

| Septone Aerosol Primer Surfacer     | TOXICITY                                 | IRRITATION                         |
|-------------------------------------|--|------------------------------------|
|                                     | Not Available                            | Not Available                      |
| toluene                             | TOXICITY                                 | IRRITATION                         |
|                                     | Dermal (rabbit) LD50: 12124 mg/kg        | Eye (rabbit): 2mg/24h - SEVERE     |
|                                     | Inhalation (rat) LC50: >26700 ppm/1h     | Eye (rabbit):0.87 mg - mild        |
|                                     | Oral (rat) LD50: 636 mg/kg               | Eye (rabbit):100 mg/30sec - mild   |
|                                     |  | Skin (rabbit):20 mg/24h-moderate   |
|                                     |  | Skin (rabbit):500 mg - moderate    |
| Not Available                       | Not Available                            |                                    |
| methyl ethyl ketone                 | TOXICITY                                 | IRRITATION                         |
|                                     | Dermal (rabbit) LD50: 20000 mg/kg        | - mild                             |
|                                     | Dermal (rabbit) LD50: 6480 mg/kg         | Eye (human): 350 ppm -irritant     |
|                                     | Inhalation (rat) LC50: 50100 mg/m3/8 hr  | Eye (rabbit): 80 mg - irritant     |
|                                     | Inhalation (rat) LD50: 23500 mg/m3/8 hr  | Skin (rabbit): 402 mg/24 hr - mild |
|                                     | Oral (rat) LD50: 2737 mg/kg              | Skin (rabbit):13.78mg/24 hr open   |
| Not Available                       | Not Available                            |                                    |
| xylene                              | TOXICITY                                 | IRRITATION                         |
|                                     | Inhalation (rat) LC50: 5000 ppm/4h       | Eye (human): 200 ppm irritant      |
|                                     | Intraperitoneal (Mouse) LD50: 1548 mg/kg | Eye (rabbit): 5 mg/24h SEVERE      |
|                                     | Intraperitoneal (Rat) LD50: 2459 mg/kg   | Eye (rabbit): 87 mg mild           |
|                                     | Oral (Mouse) LD50: 2119 mg/kg            | Skin (rabbit):500 mg/24h moderate  |
|                                     | Oral (rat) LD50: 4300 mg/kg              |                                    |
| Subcutaneous (Rat) LD50: 1700 mg/kg |  |                                    |
| Not Available                       | Not Available                            |                                    |
| ethanol                             | TOXICITY                                 | IRRITATION                         |
|                                     | Inhalation (rat) LC50: 20,000 ppm/10h    | Eye (rabbit): 500 mg SEVERE        |
|                                     | Inhalation (rat) LC50: 64000 ppm/4h      | Eye (rabbit):100mg/24hr-moderate   |
|                                     | Oral (rat) LD50: 7060 mg/kg              | Skin (rabbit):20 mg/24hr-moderate  |
|                                     | Skin (rabbit):400 mg (open)-mild         |                                    |
| Not Available                       | Not Available                            |                                    |
| methyl isobutyl ketone              | TOXICITY                                 | IRRITATION                         |
|                                     | Oral (rat) LD50: 2080 mg/kg              | Eye (human): 200 ppm/15m           |
|                                     | Oral (rat) LD50: 2460 mg/kg              | Eye (rabbit): 40 mg - SEVERE       |
|                                     |  | Eye (rabbit): 500 mg/24h - mild    |
|                                     | Skin (rabbit): 500 mg/24h - mild         |                                    |
| Not Available                       | Not Available                            |                                    |
| n-butyl acetate                     | TOXICITY                                 | IRRITATION                         |
|                                     | Dermal (rabbit) LD50: 3200 mg/kg*        | * [PPG]                            |
|                                     | Inhalation (rat) LC50: 2000 ppm/4H       | Eye ( human): 300 mg               |
|                                     | Inhalation (Rat) LC50: 390 ppm/4h        | Eye (rabbit): 20 mg (open)-SEVERE  |
|                                     | Intraperitoneal (Mouse) LD50: 1230 mg/kg | Eye (rabbit): 20 mg/24h - moderate |
|                                     | Oral (Guinea pig) LD50: 4700 mg/kg       | Skin (rabbit): 500 mg/24h-moderate |
|                                     | Oral (Rabbit) LD50: 3200 mg/kg           |                                    |
|                                     | Oral (Rat) LD50: 10768 mg/kg             |                                    |
| Oral (rat) LD50: 13100 mg/kg        |  |                                    |
| Not Available                       | Not Available                            |                                    |
| hydrocarbon propellant              | TOXICITY                                 | IRRITATION                         |
|                                     | Not Available                            | Not Available                      |

Not available. Refer to individual constituents.

|                               |   |
|-------------------------------|---|
| <b>TOLUENE</b>                | <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p> <p>For toluene:<br/><b>Acute Toxicity</b><br/>Humans exposed to intermediate to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis, and death. Similar effects are observed in short-term animal studies.<br/><b>Humans</b> - Toluene ingestion or inhalation can result in severe central nervous system depression, and in large doses, can act as a narcotic. The ingestion of about 60 mL resulted in fatal nervous system depression within 30 minutes in one reported case.</p>   |
| <b>XYLENE</b>                 | <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p> <p>The substance is classified by IARC as Group 3:<br/><b>NOT</b> classifiable as to its carcinogenicity to humans.<br/>Evidence of carcinogenicity may be inadequate or limited in animal testing.<br/>Reproductive effector in rats</p>   |
| <b>ETHANOL</b>                | <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p>   |
| <b>METHYL ISOBUTYL KETONE</b> | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.</p> |
| <b>N-BUTYL ACETATE</b>        | <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p>   |
| <b>HYDROCARBON PROPELLANT</b> | <p>No significant acute toxicological data identified in literature search.</p> <p>for Petroleum Hydrocarbon Gases:<br/>In many cases, there is more than one potentially toxic constituent in a refinery gas. In those cases, the constituent that is most toxic for a particular endpoint in an individual refinery stream is used to characterize the endpoint hazard for that stream. The hazard potential for each mammalian endpoint for each of the petroleum hydrocarbon gases is dependent upon each petroleum hydrocarbon gas constituent endpoint toxicity values (LC50, LOAEL, etc.) and the relative concentration of the constituent present in that gas. It should also be noted that for an individual petroleum hydrocarbon gas, the constituent characterizing toxicity may be different for different mammalian endpoints, again, being dependent upon the concentration of the different constituents in each, distinct petroleum hydrocarbon gas.<br/>All Hydrocarbon Gases Category members contain primarily hydrocarbons (i.e., alkanes and alkenes) and occasionally asphyxiant gases like hydrogen. The inorganic components of the petroleum hydrocarbon gases are less toxic than the C1 - C4 and C5 - C6 hydrocarbon components to both mammalian and aquatic organisms.</p>                 |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✔ | <b>Carcinogenicity</b>          | ⊘ |
| <b>Skin Irritation/Corrosion</b>         | ⊘ | <b>Reproductivity</b>           | ✔ |
| <b>Serious Eye Damage/Irritation</b>     | ✔ | <b>STOT - Single Exposure</b>   | ✔ |
| <b>Respiratory or Skin sensitisation</b> | ⊘ | <b>STOT - Repeated Exposure</b> | ✔ |
| <b>Mutagenicity</b>                      | ⊘ | <b>Aspiration Hazard</b>        | ⊘ |

**CMR STATUS**

|                   |                        |  |          |
|-------------------|------------------------|--|----------|
| <b>CARCINOGEN</b> | hydrocarbon propellant | Australia Exposure Standards - Carcinogens | Carc. 1B |
| <b>SKIN</b>       | toluene                | Australia Exposure Standards - Skin        | Sk       |

**SECTION 12 ECOLOGICAL INFORMATION****Toxicity**

**DO NOT discharge into sewer or waterways.**

Avoid release of contents into the environment. The propellant will vapourise rapidly when released into the atmosphere. The propellant will photochemically decompose under atmospheric conditions. This product does not contain CFCs.

**Persistence and degradability**

| Ingredient    | Persistence: Water/Soil | Persistence: Air |
|---------------|-------------------------|------------------|
| Not Available | Not Available           | Not Available    |

**Bioaccumulative potential**

| Ingredient    | Bioaccumulation |
|---------------|-----------------|
| Not Available | Not Available   |

**Mobility in soil**

| Ingredient    | Mobility      |
|---------------|---------------|
| Not Available | Not Available |

**SECTION 13 DISPOSAL CONSIDERATIONS****Waste treatment methods**

| Product / Packaging disposal | Disposal methods  |
|------------------------------|---|
|                              | <ul style="list-style-type: none"> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Discharge contents of damaged aerosol cans at an approved site.</li> <li>▶ Allow small quantities to evaporate.</li> <li>▶ <b>DO NOT incinerate or puncture aerosol cans.</b></li> <li>▶ Bury residues and emptied aerosol cans at an approved site.</li> </ul> |

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

|                  |  |
|------------------|--|
|                  |  |
| Marine Pollutant | NO   |
| HAZCHEM          | 2YE  |

**Land transport (ADG)**

|                              |  |
|------------------------------|--|
| UN number                    | 1950   |
| Packing group                | Not Available  |
| UN proper shipping name      | AEROSOLS   |
| Environmental hazard         | No relevant data   |
| Transport hazard class(es)   | Class : 2.1<br>Subrisk :   |
| Special precautions for user | Special provisions : 63 190 277 327<br>limited quantity : See SP 277 |

**Air transport (ICAO-IATA / DGR)**

|                              |  |
|------------------------------|--|
| UN number                    | 1950   |
| Packing group                | Not Available  |
| UN proper shipping name      | Aerosols, flammable  |
| Environmental hazard         | No relevant data   |
| Transport hazard class(es)   | ICAO/IATA Class : 2.1<br>ICAO / IATA Subrisk :<br>ERG Code : 10L   |
| Special precautions for user | Special provisions : A145A167A802<br>Cargo Only Packing Instructions : 203<br>Cargo Only Maximum Qty / Pack : 150 kg<br>Passenger and Cargo Packing Instructions : 203<br>Passenger and Cargo Maximum Qty / Pack : 75 kg<br>Passenger and Cargo Limited Quantity Packing Instructions : Y203<br>Passenger and Cargo Limited Maximum Qty / Pack : 30 kg G |

**Sea transport (IMDG-Code / GGVSee)**

## Septone Aerosol Primer Surfacer

|                                     |   |
|-------------------------------------|---|
| <b>UN number</b>                    | 1950  |
| <b>Packing group</b>                | Not Available   |
| <b>UN proper shipping name</b>      | AEROSOLS  |
| <b>Environmental hazard</b>         |   |
| <b>Transport hazard class(es)</b>   | IMDG Class : 2.1<br>IMDG Subrisk :  |
| <b>Special precautions for user</b> | EMS Number : F-D,S-U<br>Special provisions : 63 190 277 327 344 959<br>Limited Quantities : SP277 |

## Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

| Source                   | Ingredient | Pollution Category | Residual Concentration - Outside Special Area (% w/w) | Residual Concentration |
|--------------------------|------------|--------------------|---|------------------------|
| 40-7-4-9-0-0-MK-20041022 | ethanol    | Not Available      | Not Available   | Not Available          |

## SECTION 15 REGULATORY INFORMATION

## Safety, health and environmental regulations / legislation specific for the substance or mixture

|   |  |
|---|--|
| <p><b>toluene(108-88-3) is found on the following regulatory lists</b></p>            | <p>"Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Customs (Prohibited Exports) Regulations 1958 - Schedule 9 Precursor substances - Part 2", "Australia Illicit Drug Reagents/Essential Chemicals - Category III", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "OSPAR List of Chemicals for Priority Action", "Australia Exposure Standards", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II", "FisherTransport Information", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Australia Inventory of Chemical Substances (AICS)", "OECD List of High Production Volume (HPV) Chemicals", "International Fragrance Association (IFRA) Standards Prohibited", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (Aquatic habitat)", "UNECE - Kiev Protocol on Pollutant Release and Transfer Registers - Annex II", "Australia National Pollutant Inventory", "Sigma-AldrichTransport Information", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia High Volume Industrial Chemical List (HVICL)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water", "OECD Existing Chemicals Database", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Hazardous Substances Information System - Consolidated Lists", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (AQUA/1 to 6 - non-pesticide anthropogenic organics)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "IMO IBC Code Chapter 17: Summary of minimum requirements", "United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control (Red List) - Table II", "Acros Transport Information", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6"</p> |
| <p><b>methyl ethyl ketone(78-93-3) is found on the following regulatory lists</b></p> | <p>"Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Illicit Drug Reagents/Essential Chemicals - Category III", "Australia Customs (Prohibited Exports) Regulations 1958 - Schedule 9 Precursor substances - Part 2", "IOFI Global Reference List of Chemically Defined Substances", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Exposure Standards", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II", "FisherTransport Information", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Australia Inventory of Chemical Substances (AICS)", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "Australia National Pollutant Inventory", "Sigma-AldrichTransport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "Australia High Volume Industrial Chemical List (HVICL)", "OECD Existing Chemicals Database", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Hazardous Substances Information System - Consolidated Lists", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "IMO IBC Code Chapter 17: Summary of minimum requirements", "United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control (Red List) - Table II", "International Fragrance Association (IFRA) Survey: Transparency List"</p>   |
| <p><b>xylene(1330-20-7) is found on the following regulatory lists</b></p>            | <p>"Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "International Maritime Dangerous Goods Requirements (IMDG Code)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "OSPAR List of Chemicals for Priority Action", "Australia Exposure Standards", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "FisherTransport Information", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Australia</p>  |

|   |   |
|---|---|
|   | <p>Standards for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "UNECE - Kiev Protocol on Pollutant Release and Transfer Registers - Annex II", "Australia National Pollutant Inventory", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia High Volume Industrial Chemical List (HVICL)", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "OECD Existing Chemicals Database", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "IMO IBC Code Chapter 17: Summary of minimum requirements", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7", "International Fragrance Association (IFRA) Survey: Transparency List", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6"</p>  |
| <p><b>ethanol(64-17-5) is found on the following regulatory lists</b></p>                   | <p>"International Maritime Dangerous Goods Requirements (IMDG Code)", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Particular Sports (French)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "IOFI Global Reference List of Chemically Defined Substances", "WHO Model List of Essential Medicines - Adults", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Particular Sports (Korean)", "Australia Exposure Standards", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "FisherTransport Information", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Australia Inventory of Chemical Substances (AICS)", "OECD List of High Production Volume (HPV) Chemicals", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix B (Part 3)", "OSPAR National List of Candidates for Substitution - Norway", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "Australia National Pollutant Inventory", "UNECE - Kiev Protocol on Pollutant Release and Transfer Registers - Annex II", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Competition (German)", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "Sigma-AldrichTransport Information", "World Anti-Doping Agency - The 2014 Prohibited List World Anti-Doping Code - Substances Prohibited in Particular Sports", "Australia High Volume Industrial Chemical List (HVICL)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "OECD Existing Chemicals Database", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Hazardous Substances Information System - Consolidated Lists", "FEMA Generally Recognized as Safe (GRAS) Flavoring Substances 23 - Examples of FEMA GRAS Substances with Non-Flavor Functions", "IMO IBC Code Chapter 17: Summary of minimum requirements", "Acros Transport Information", "International Fragrance Association (IFRA) Survey: Transparency List"</p> |
| <p><b>methyl isobutyl ketone(108-10-1) is found on the following regulatory lists</b></p>   | <p>"Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "International Maritime Dangerous Goods Requirements (IMDG Code)", "IOFI Global Reference List of Chemically Defined Substances", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Exposure Standards", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "FisherTransport Information", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "OECD List of High Production Volume (HPV) Chemicals", "Australia Inventory of Chemical Substances (AICS)", "OSPAR National List of Candidates for Substitution - Norway", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "Australia National Pollutant Inventory", "Sigma-AldrichTransport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "OECD Existing Chemicals Database", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Hazardous Substances Information System - Consolidated Lists", "International Air Transport Association (IATA) Dangerous Goods Regulations", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Fragrance Association (IFRA) Survey: Transparency List"</p>   |
| <p><b>n-butyl acetate(123-86-4) is found on the following regulatory lists</b></p>          | <p>"International Maritime Dangerous Goods Requirements (IMDG Code)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "IOFI Global Reference List of Chemically Defined Substances", "Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 2", "Australia Exposure Standards", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "FisherTransport Information", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Australia Inventory of Chemical Substances (AICS)", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "Australia National Pollutant Inventory", "Sigma-AldrichTransport Information", "Australia High Volume Industrial Chemical List (HVICL)", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "OECD Existing Chemicals Database", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Hazardous Substances Information System - Consolidated Lists", "International Air Transport Association (IATA) Dangerous Goods Regulations", "IMO IBC Code Chapter 17: Summary of minimum requirements", "Acros Transport Information", "International Fragrance Association (IFRA) Survey: Transparency List"</p>   |
| <p><b>hydrocarbon propellant(68476-85-7) is found on the following regulatory lists</b></p> | <p>"Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 1", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia Exposure Standards", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Hazardous Chemicals at Major Hazard Facilities (and their Threshold Quantity) - Table 15.1", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia - New South Wales -Work Health and Safety Regulation 2011 - Hazardous chemicals", "Australia - South Australia - Work Health and Safety Regulations 2012 - Schedule 15—Hazardous chemicals at major hazard facilities (and their threshold quantity) Table 15.1", "Australia - New South Wales - Work Health and Safety Regulation 2011 - Hazardous chemicals at major hazard facilities (and their threshold quantity) - Table 15.1", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (English)", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Australia Inventory of Chemical Substances (AICS)", "OECD List of High Production Volume (HPV) Chemicals", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "International Chemical Secretariat (ChemSec) SIN List (*Substitute It Now!)", "International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft", "Australia Dangerous Goods Code (ADG Code) - Packing Instruction - Liquefied and Dissolved Gases", "United Nations Recommendations on the Transport of Dangerous Goods Model Regulations (Spanish)", "Australia High Volume Industrial Chemical List (HVICL)", "Australia - Queensland Work Health and Safety Regulation - Hazardous chemicals at major hazard facilities (and their threshold quantity)", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Work Health and Safety Regulations 2011 - Hazardous chemicals at major hazard facilities and their threshold quantity", "Australia Hazardous Substances Information System - Consolidated Lists", "International Air Transport Association (IATA) Dangerous Goods Regulations"</p>   |

## SECTION 16 OTHER INFORMATION

---

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references)

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.