Septone Oilsolve Degreaser

ITW (ITW AAMTech)

Chemwatch: **4879-93** Version No: **3.1.1.1**

Safety Data Sheet according to WHS and ADG requirements

Issue Date: **10/12/2013** Print Date: **10/12/2013** S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Septone Oilsolve Degreaser
Chemical Name	Not Applicable
Synonyms	Product Codes: ADO20, ADO200
Proper shipping name	PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S. (see 3.2.5 for relevant [AUST.] entries) (contains naphtha, petroleum, hydrodesulfurised heavy)
Chemical formula	Not Applicable
Other means of identification	Not Available
CAS number	Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Use according to manufacturer's directions. , Solvent degreaser.

Details of the supplier of the safety data sheet

Registered company name	ITW (ITW AAMTech)	1	
Address	100 Hassall Street Wetherill Park 2164 NSW Australia	1 1 1 1 1	
Telephone	+61 2 9828 0900		
Fax	+61 2 9725 4698	1 1 1	1
Website	Not Available		
Email	Not Available		

Emergency telephone number

Association / Organisation	Not Available	
Emergency telephone numbers	1800 039 008 (24 hours)	
Other emergency telephone numbers	+61 3 9573 3112 (24 hours)	

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

 ${\sf HAZARDOUS\ CHEMICAL.\ DANGEROUS\ GOODS.\ According\ to\ the\ Model\ WHS\ Regulations\ and\ the\ ADG\ Code.}$

Poisons Schedule		
GHS Classification ^[1]		
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Regolamento 1272/2008 - Annex VI	

Label elements

GHS label elements





SIGNAL WORD

DANGER

Hazard statement(s)

• •	
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways

Precautionary statement(s) Prevention

Treductionary Statement(3) Trevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P233	Keep container tightly closed.	
P240	Ground/bond container and receiving equipment.	

Chemwatch: **4879-93**Version No: **3.1.1.1**

Page 2 of 8 Septone Oilsolve Degreaser

Issue Date: 10/12/2013 Print Date: 10/12/2013

P241 Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.	
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P301+P310+P331 IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider. Do NOT induce vomiting.	
P370+P378	In case of fire: Use to extinguish.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64742-82-1.	98	naphtha, petroleum, hydrodesulfurised heavy
71-43-2	<0.1	benzene

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If furnes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- ▶ Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use of cuffed endotracheal tube in adult patients. [Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Chemwatch: 4879-93 Page 3 of 8 Issue Date: 10/12/2013 Version No. 3.1.1.1 Print Date: 10/12/2013

Septone Oilsolve Degreaser

Foam Dry chemical powder BCF (where regulations permit). Carbon dioxide. Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Alert Fire Brigade and tell them location and nature of hazard.

Advice for firefighters

May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. If safe, switch off electrical equipment until vapour fire hazard removed. Fire Fighting Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools.

- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

Fire/Explosion Hazard

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include:

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

7. 7		
Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb small quantities with vermiculite or other absorbent material. Wipe up. Collect residues in a flammable waste container. 	
Major Spills	Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. Contain spill with sand, earth or vermiculite. Use only spark-free shovels and explosion proof equipment. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.	
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.	

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin
- Electrostatic discharge may be generated during pumping this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until fill pipe submerged to twice its

Safe handling

- Avoid splash filling. Do NOT use compressed air for filling discharging or handling operations.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.

diameter, then <= 7 m/sec).

- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.

Chemwatch: **4879-93** Page **4** of **8**

Version No: 3.1.1.1

Page 4 of 8 Issue Date: 10/12/2013
Septone Oilsolve Degreaser Print Date: 10/12/2013

Avoid smoking, naked lights or ignition sources.

- Avoid generation of static electricity.
- DO NOT use plastic buckets
- Earth all lines and equipment.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- When handling, **DO NOT** eat, drink or smoke
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
 - Store away from incompatible materials in a cool, dry well ventilated area.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storage and handling recommendations contained within this MSDS.

Conditions for safe storage, including any incompatibilities

Other information

Packing as supplied by manufacturer.

Plastic containers may only be used if approved for flammable liquid.

Check that containers are clearly labelled and free from leaks.

Storage incompatibility

Avoid reaction with oxidising agents

PACKAGE MATERIAL INCOMPATIBILITIES

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	benzene	Benzene	3.2 (mgm3) / 1 (ppm)	Not Available	Not Available	Not Available

EMERGENCY LIMITS

ingredient	IEEL-0	TEEL-1	IEEL-2	TEEL-3
benzene	1(ppm)	52(ppm)	800(ppm)	4000(ppm)

Ingredient	Original IDLH	Revised IDLH
benzene	3,000(ppm)	500(ppm)

Exposure controls

Appropriate engineering controls Use in a v

Use in a well-ventilated area

General exhaust is adequate under normal operating conditions.

Personal protection









reisonal protection

Safety glasses with side shields.Chemical goggles.

Eye and face protection

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]

Skin protection

ction See Hand protection below

Hand protection

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

Body protection

See Other protection below

- Overalls.PVC Apron.
- PVC Apron.PVC protective suit may be required if exposure severe.

Other protection

- Eyewash unit.Ensure there is ready access to a safety shower.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.

Septone Oilsolve Degreaser

Issue Date: **10/12/2013**Print Date: **10/12/2013**

For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

Thermal hazards

Respiratory protection

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Septone Oilsolve Degreaser Not Available

Material CPI

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as

"feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear green flammable liquid with aromatic odour; does not mix with water.		
Physical state	Liquid	Relative density (Water = 1)	0.80
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	145-300	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	38 (Abel)	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	6.0	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.0	Volatile Component (%vol)	100
Vapour pressure (kPa)	0.3 @ 20C	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution(1%)	Not Applicable
Vapour density (Air = 1)	4.35		

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.
Ingestion	Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.
Skin Contact	Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the

Chemwatch: 4879-93 Version No: 3.1.1.1

Page 6 of 8

Septone Oilsolve Degreaser

Issue Date: 10/12/2013 Print Date: 10/12/2013

	microscopic level there may be intercellular The material may accentuate any pre-existi	oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. ng dermatitis condition	
Еуе	Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.		
Chronic	loss, tremor in the fingers and tongue, verti anaemia and degenerative changes in the li associated with visual disturbances, damag psychological and neurophysiological defici involvement. Chronic dermal exposure to p and erosion may also increase susceptibilit reported elevations in standard mortality ra workplace exposure to petroleum or one of finding.	hydrocarbons may produce narcosis with dizziness, weakness, irritability, concentration and/or memory igo, olfactory disorders, constriction of visual field, paraesthesias of the extremities, weight loss and iver and kidney. Chronic exposure by petroleum workers, to the lighter hydrocarbons, has been ge to the central nervous system, peripheral neuropathies (including numbness and paraesthesias), its, bone marrow toxicities (including hypoplasia possibly due to benzene) and hepatic and renal etroleum hydrocarbons may result in defatting which produces localised dermatoses. Surface cracking y to infection by microorganisms. One epidemiological study of petroleum refinery workers has tios for skin cancer along with a dose-response relationship indicating an association between routine its constituents and skin cancer, particularly melanoma. Other studies have been unable to confirm this esult in nervous system impairment and liver and blood changes. [PATTYS]	
	TOXICITY	IRRITATION	
Septone Oilsolve Degreaser	TOXICITY Oral (Rat) LD50: >2000 mg/kg	IRRITATION Not Available	
Septone Oilsolve Degreaser naphtha, petroleum, hydrodesulfurised			
, ,	Oral (Rat) LD50: >2000 mg/kg	Not Available	
naphtha, petroleum, hydrodesulfurised	Oral (Rat) LD50: >2000 mg/kg	Not Available IRRITATION	
naphtha, petroleum, hydrodesulfurised	Oral (Rat) LD50: >2000 mg/kg TOXICITY Not Available	Not Available IRRITATION Not Available	

^{*} Value obtained from manufacturer's msds unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

Not Available

Septone Oilsolve Degreaser	[* Manufacturer]		
NAPHTHA, PETROLEUM, HYDRODESULFURISED HEAVY	No significant acute toxicological data identified in literature search.		
BENZENE	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.		
Acute Toxicity	Not Applicable	Carcinogenicity	Not Applicable
Skin Irritation/Corrosion	Not Applicable	Reproductivity	Not Applicable
Serious Eye Damage/Irritation	Not Applicable	STOT - Single Exposure	Not Applicable
Respiratory or Skin sensitisation	Not Applicable	STOT - Repeated Exposure	Not Applicable
Mutagenicity	Not Applicable	Aspiration Hazard	Aspiration Hazard Category 1
CMR STATUS	6		

Not Available

REPROTOXIN	benzene ILO Chemicals in the electronics industry that have toxic effects on reproduction H si
CARCINOGEN	benzene Australia Exposure Standards - Carcinogens Carc. 1A

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Biodegradable

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Not Available	Not Available	Not Available

Bioaccumulative potential

Ingredient	Bioaccumulation
Not Available	Not Available

Septone Oilsolve Degreaser

Issue Date: 10/12/2013 Print Date: 10/12/2013

Ingredient	Mobility
Not Available	Not Available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- $\ ^{\Vdash}$ Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant: NO

HAZCHEM 3YE; 3Y

Land transport (ADG)			
UN number	1268		
Packing group	III		
UN proper shipping name (contains naphtha, petroleum, hydrodesulfurised heavy)	PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S. (see 3.2.5 for relevant [AUST.] entries)		
Environmental hazard	No relevant data		
Transport hazard class(es)	Class 3 Subrisk		
Special precautions for user	Special provisions 223 AU02 limited quantity 5 L		

Air transport (ICAO-IATA / DGR)

UN number	1268	
Packing group	Ш	
UN proper shipping name	Petroleum distillates, n.o.s.; Petroleum products, n.o.s. (contains	naphtha, petroleum, hydrodesulfurised heavy)
Environmental hazard	No relevant data	
Transport hazard class(es)	ICAO/IATA Class 3 ICAO / IATA Subrisk ERG Code 3L	
Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions Passenger and Cargo Maximum Qty / Pack	A3 366 220 L 355 60 L Y344 10 L

Sea transport (IMDG-Code / GGVSee)

UN number	1268
Packing group	III
UN proper shipping name	PETROLEUM DISTILLATES, N.O.S. or PETROLEUM PRODUCTS, N.O.S. (contains naphtha, petroleum, hydrodesulfurised heavy)
Environmental hazard	No relevant data
Transport hazard class(es)	IMDG Class 3 IMDG Subrisk

Page 8 of 8 Septone Oilsolve Degreaser

Issue Date: 10/12/2013
Print Date: 10/12/2013

Special precautions for user

EMS Number	F-E,S-E
Special provisions	223 955
Limited Quantities	5 L

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

naphtha, petroleum, hydrodesulfurised heavy(64742-82-1.) is found on the following regulatory lists "Australia Inventory of Chemical Substances (AICS)", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD List of High Production Volume (HPV) Chemicals", "Australia High Volume Industrial Chemical List (HVICL)", "International Chemical Secretariat (ChemSec) SIN List ("Substitute It Now!)", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods Page Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)", "International Air Transport Association (IATA) Dangerous Goods Regulations", "International Maritime Dangerous Goods Requirements (IMDG Code)", "Australia - New South Wales Protection of the Environment Operations (Waste) Regulation 2005 - Characteristics of trackable wastes", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List"

benzene(71-43-2) is found on the

following regulatory lists

"Australia Inventory of Chemical Substances (AICS)", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Fragrance Association (IFRA) Standards Prohibited", "OECD List of High Production Volume (HPV) Chemicals", "Australia High Volume Industrial Chemical List (HVICL)", "International Chemical Secretariat (ChemSec) SIN List (*Substitute It Now!)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "Sigma-AldrichTransport Information", "Acros Transport Information", "IMO IBC Code Chapter 17: Summary of minimum requirements", "Australia Australian Safety and Compensation Council (ASCC) Draft National Code of Practice for the Control of Workplace Hazardous Chemicals - Schedule 5 Restricted hazardous chemicals", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia Occupational Health and Safety (Commonwealth Employment) (National Standards) Regulations 1994 - Hazardous Substances Requiring Health Surveillance", "Australia - Western Australia Hazardous Substances Requiring Health Surveillance", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water". "Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)","Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (AQUA/1 to 6 - non-pesticide anthropogenic organics)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm (Aquatic habitat)", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics","Australia National Pollutant Inventory","Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality","Australia - New South Wales - Work Health and Safety Regulation 2011 - Requirements for health monitoring -Hazardous chemicals (other than lead) requiring health monitoring", "Australia - New South Wales - Work Health and Safety Regulation 2011 Restricted hazardous chemicals", "Australia - Queensland Work Health and Safety Regulation - Restricted hazardous chemicals", "Australia - Queensland Health (Drugs and Poisons) Regulation 1996 - Appendix 7: Regulated poisons","Australia - Tasmania - Work Health and Safety Regulations 2012 - Requirements for Health Monitoring - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Restricted hazardous chemicals","Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7","Australia - New South Wales Hazardous Substances Requiring Health Surveillance", "Australia - New South Wales Hazardous Substances Prohibited for Specific Uses", "Australia - Tasmania Hazardous Substances Requiring Health Surveillance", "Australia - Northern Territories Work Health and Safety National Uniform Legislation Regulations- Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring","Australia - Northern Territories Work Health and Safety National Uniform Legislation Regulations- Restricted hazardous chemicals", "Australia - South Australia - Work Health and Safety Regulations 2012 - Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - South Australia - Work Health and Safety Regulations 2012 - Restricted hazardous chemicals", "Australia - Northern Territories Work Health and Safety National Uniform Legislation Regulations- Restricted carcinogens", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Restricted carcinogens", "Australia - South Australia - Work Health and Safety Regulations 2012 - Restricted carcinogens". "Australia - New South Wales Work Health and Safety Regulation 2011 Restricted carcinogens", "Australia - Queensland Work Health and Safety Regulation - Restricted Carcinogens", "Australia Work Health and Safety Regulations 2011 - Restricted carcinogens", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Appendix E (Part 2)", "Australia Occupational Health and Safety (Commonwealth Employment) (National Standards) Regulations 1994 -Scheduled Carcinogenic Substance", "Australia - Western Australia Carcinogenic substances to be used only for purposes approved by the Commissioner", "Australia - New South Wales Notifiable Carcinogens", "Australia Exposure Standards", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix J (Part 2)", "Australia Hazardous Substances Requiring Health Surveillance", "Australia - Queensland Work Health and Safety Regulation - Hazardous chemicals (other than lead) requiring health monitoring","Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)","Australia Work Health and Safety Regulations 2011 - Hazardous chemicals (other than lead) requiring health monitoring", "Australia Work Health and Safety Regulations 2011 - Restricted hazardous chemicals", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments", "Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes", "Belgium Federal Public Service Mobility and Transport, Regulations concerning the International Carriage of Dangerous Goods by Rail - Table A: Dangerous Goods List - RID 2013 (Dutch)","International Air Transport Association (IATA) Dangerous Goods Regulations", "International Maritime Dangerous Goods Requirements (IMDG Code)", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5","Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "OSPAR List of Chemicals for Priority Action"

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.