

Permatex The Right Stuff 1 Minute Gasket

ITW AAMTech

Chemwatch: 16-1392

Version No: 5.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 08/09/2014

Print Date: 12/05/2015

Initial Date: **Not Available**

S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Permatex The Right Stuff 1 Minute Gasket
Synonyms	PX25229
Proper shipping name	AEROSOLS
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Application is by spray atomisation from a hand held aerosol pack Elastomeric rubber; sealant; gasket.
---------------------------------	---

Details of the manufacturer/importer

Registered company name	ITW AAMTech	ITW AAMTech
Address	100 Hassall Street 2164 NSW Australia	Unit 2/38 Trugood Drive 2013 New Zealand
Telephone	1800 177 989	+64 9272 1940
Fax	1800 308 556	+64 9272 1949
Website	www.aamtech.com.au	www.aamtech.co.nz
Email	info@aamtech.com.au	info@aamtech.co.nz

Emergency telephone number

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	1800 039 008	+800 2436 2255
Other emergency telephone numbers	+61 3 9573 3112	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
GHS Classification ^[1]	Skin Corrosion/Irritation Category 2, Eye Irritation Category 2, Skin Sensitizer Category 1, STOT - SE (Resp. Irr.) Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	
---------------------------	---

Permatex The Right Stuff 1 Minute Gasket

SIGNAL WORD

WARNING

Hazard statement(s)

H315	Causes skin irritation
H319	Causes serious eye irritation
H317	May cause an allergic skin reaction
H335	May cause respiratory irritation
AUH044	Risk of explosion if heated under confinement

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary statement(s) Response

P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P302+P352	IF ON SKIN: Wash with plenty of water and soap
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
471-34-1	25-50	<u>calcium carbonate</u>
70131-67-8	20-40	<u>dimethylsiloxane, hydroxy-terminated</u>
63148-62-9	5-20	<u>polydimethylsiloxane</u>
2224-33-1	<5	<u>vinyltris(methylethylketoxime)silane</u>
57-11-4	<3	<u>stearic acid</u>
7727-37-9	<2	<u>nitrogen</u>
Not Available	NotSpec.	on curing will react with moisture to release
96-29-7	NotSpec.	<u>methyl ethyl ketoxime</u>

on curing will react with moisture to release

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
-------------	--

Continued...

Permatex The Right Stuff 1 Minute Gasket

	<ul style="list-style-type: none"> ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If solids or aerosol mists are deposited upon the skin:</p> <ul style="list-style-type: none"> ▶ Flush skin and hair with running water (and soap if available). ▶ Remove any adhering solids with industrial skin cleansing cream. ▶ DO NOT use solvents. ▶ Seek medical attention in the event of irritation.
Inhalation	<p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> ▶ Remove to fresh air. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	Not considered a normal route of entry.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

	<p>SMALL FIRE:</p> <ul style="list-style-type: none"> ▶ Water spray, dry chemical or CO2 <p>LARGE FIRE:</p> <ul style="list-style-type: none"> ▶ Water spray or fog.
--	--

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered to be a significant fire risk. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ Aerosol cans may explode on exposure to naked flames.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Wear protective clothing, impervious gloves and safety glasses. ▶ Shut off all possible sources of ignition and increase ventilation.
Major Spills	<ul style="list-style-type: none"> ▶ Silicone fluids, even in small quantities, may present a slip hazard. ▶ It may be necessary to rope off area and place warning signs around perimeter. ▶ Clean up area from spill, with suitable absorbant, as soon as practically possible. ▶ Final cleaning may require use of steam, solvents or detergents.
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps.
----------------------	--

Continued...

Permatex The Right Stuff 1 Minute Gasket

Other information

- ▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can

Conditions for safe storage, including any incompatibilities

Suitable container

- ▶ Aerosol dispenser.
- ▶ Check that containers are clearly labelled.

Storage incompatibility

- ▶ Avoid reaction with oxidising agents

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	calcium carbonate	Calcium carbonate (a)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	stearic acid	Stearates (a) (d)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nitrogen	Nitrogen	Not Available	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
calcium carbonate	Limestone; (Calcium carbonate; Dolomite)	27 mg/m3	27 mg/m3	1300 mg/m3
calcium carbonate	Carbonic acid, calcium salt	45 mg/m3	210 mg/m3	1300 mg/m3
dimethylsiloxane, hydroxy-terminated	Dimethyl(polysiloxane); (Polydimethylsiloxane, silanol terminated; Dimethylsiloxane, poly, hydroxy end-blocked)	190 mg/m3	2100 mg/m3	13000 mg/m3
polydimethylsiloxane	Dimethyl siloxane; (Dimethylpolysiloxane; Syltherm XLT; Syltherm 800; Silicone 360)	1.5 mg/m3	16 mg/m3	990 mg/m3
stearic acid	Octadecanoic acid, n-; (Stearic acid)	0.13 mg/m3	1.4 mg/m3	8.5 mg/m3
nitrogen	Nitrogen	7.96E+05 ppm	832000 ppm	869000 ppm
methyl ethyl ketoxime	Butanone oxime; (Ethyl methyl ketoxime)	10 ppm	10 ppm	52 ppm

Ingredient	Original IDLH	Revised IDLH
calcium carbonate	Not Available	Not Available
dimethylsiloxane, hydroxy-terminated	Not Available	Not Available
polydimethylsiloxane	Not Available	Not Available
vinyltris(methylethylketoxime)silane	Not Available	Not Available
stearic acid	Not Available	Not Available
nitrogen	Not Available	Not Available
on curing will react with moisture to release	Not Available	Not Available
methyl ethyl ketoxime	Not Available	Not Available

Exposure controls


Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Continued...

Permatex The Right Stuff 1 Minute Gasket

	Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	NOTE: <ul style="list-style-type: none"> ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. ▶ No special equipment needed when handling small quantities.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: <ul style="list-style-type: none"> ▶ Overalls. ▶ Skin cleansing cream. ▶ Eyewash unit.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Permatex The Right Stuff 1 Minute Gasket Not Available

Material	CPI
----------	-----

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Black paste with a mild odour; not miscible with water. Will react with moisture during curing process.		
Physical state	Non Slump Paste	Relative density (Water = 1)	1.34
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7-8	Decomposition temperature	Not Available

Continued...

Permatex The Right Stuff 1 Minute Gasket

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Applicable	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>93	Taste	Not Available
Evaporation rate	<1 BuAC = 1	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	<3 (VOC - by wt)
Vapour pressure (kPa)	<0.7	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	3.0	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Elevated temperatures. ▶ Presence of open flame. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	<p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>There is some evidence to suggest that the material can cause respiratory irritation in some persons.</p>
Ingestion	<p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Not normally a hazard due to physical form of product.</p> <p>Considered an unlikely route of entry in commercial/industrial environments</p> <p>Silicone fluids do not have a high acute toxicity. They may have a laxative effect and produce central nervous system depression.</p>
Skin Contact	<p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p> <p>There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p> <p>Spray mist may produce discomfort</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.</p>
Eye	<p>There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.</p> <p>Not considered to be a risk because of the extreme volatility of the gas.</p>
Chronic	<p>There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p>

Permatex The Right Stuff 1 Minute Gasket

Permatex The Right Stuff 1 Minute Gasket	TOXICITY	IRRITATION
	Not Available	Not Available
calcium carbonate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 0.75 mg/24h - SEVERE
	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-moderate
dimethylsiloxane, hydroxy-terminated	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >15520 mg/kg ^[2]	Not Available
	Inhalation (rat) LC50: >8.75 mg/L/7H ^[2]	
	Oral (rat) LD50: >62080 mg/kg*d ^[2]	
polydimethylsiloxane	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye (rabbit): 100 mg/1h - mild
	Oral (rat) LD50: >17000 mg/kg ^[2]	
vinyltris(methylethylketoxime)silane	TOXICITY	IRRITATION
	Not Available	Not Available
stearic acid	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Skin (human): 75 mg/3d-I-mild
	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-moderate
nitrogen	TOXICITY	IRRITATION
	Not Available	Not Available
methyl ethyl ketoxime	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >184<2 mg/kg ^[1]	Eye (rabbit): 0.1 ml - SEVERE
	Inhalation (rat) LC50: 20 mg/l/4h ** ^[2]	
	Oral (rat) LD50: >900 mg/kg ^[1]	

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's msds. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

CALCIUM CARBONATE	No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic effects.
DIMETHYLSILOXANE, HYDROXY-TERMINATED	Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility. * [Mobay Chemical Corp] **[GE]
POLYDIMETHYLSILOXANE	Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility. The material may be irritating to the eye, with prolonged contact causing inflammation. No toxic response noted during 90 day subchronic inhalation toxicity studies The no observable effect level is 450 mg/m3. Non-irritating and non-sensitising in human patch test. [Xerox]*
STEARIC ACID	Equivocal tumorigen by RTEC criteria
NITROGEN	No significant acute toxicological data identified in literature search.
METHYL ETHYL KETOXIME	Mammalian lymphocyte mutagen *Huls Canada ** Merck
Permatex The Right Stuff 1 Minute Gasket & VINYLTRIS(METHYLETHYLKETOXIME)SILANE & METHYL ETHYL KETOXIME	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.

Continued...

Permatex The Right Stuff 1 Minute Gasket

Acute Toxicity	☹	Carcinogenicity	☹
Skin Irritation/Corrosion	✓	Reproductivity	☹
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	☹
Mutagenicity	☹	Aspiration Hazard	☹

Legend: ✓ – Data required to make classification available
 ✗ – Data available but does not fill the criteria for classification
 ☹ – Data Not Available to make classification

CMR STATUS

Not Applicable

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
stearic acid	LOW	LOW
methyl ethyl ketoxime	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
stearic acid	LOW (LogKOW = 8.23)
methyl ethyl ketoxime	LOW (BCF = 6)

Mobility in soil

Ingredient	Mobility
stearic acid	LOW (KOC = 11670)
methyl ethyl ketoxime	LOW (KOC = 130.8)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> Consult State Land Waste Management Authority for disposal. Discharge contents of damaged aerosol cans at an approved site. Allow small quantities to evaporate. DO NOT incinerate or puncture aerosol cans.
------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO
HAZCHEM	2YE

Land transport (ADG)

UN number	1950
Packing group	Not Applicable
UN proper shipping name	AEROSOLS

Continued...

Permatex The Right Stuff 1 Minute Gasket

Environmental hazard	No relevant data	
Transport hazard class(es)	Class	2.2
	Subrisk	Not Applicable
Special precautions for user	Special provisions	63 190 277 327 344
	Limited quantity	See SP 277

Air transport (ICAO-IATA / DGR)

UN number	1950	
Packing group	Not Applicable	
UN proper shipping name	Aerosols, non-flammable	
Environmental hazard	No relevant data	
Transport hazard class(es)	ICAO/IATA Class	2.2
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	2L
Special precautions for user	Special provisions	A98A145A167A802
	Cargo Only Packing Instructions	203
	Cargo Only Maximum Qty / Pack	150 kg
	Passenger and Cargo Packing Instructions	203
	Passenger and Cargo Maximum Qty / Pack	75 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Y203
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

UN number	1950	
Packing group	Not Applicable	
UN proper shipping name	AEROSOLS	
Environmental hazard	Not Applicable	
Transport hazard class(es)	IMDG Class	2.2
	IMDG Subrisk	Not Applicable
Special precautions for user	EMS Number	F-D , S-U
	Special provisions	63 190 277 327 344 959
	Limited Quantities	See SP277

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	polydimethylsiloxane	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	stearic acid	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	methyl ethyl ketoxime	Y

Permatex The Right Stuff 1 Minute Gasket

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

calcium carbonate(471-34-1) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)"
dimethylsiloxane, hydroxy-terminated(70131-67-8) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)"
polydimethylsiloxane(63148-62-9) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)"
vinyltris(methylethylketoxime)silane(2224-33-1) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)"
stearic acid(57-11-4) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)"
nitrogen(7727-37-9) is found on the following regulatory lists	"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)"
methyl ethyl ketoxime(96-29-7) is found on the following regulatory lists	"Australia Inventory of Chemical Substances (AICS)", "Australia Hazardous Substances Information System - Consolidated Lists"

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	N (dimethylsiloxane, hydroxy-terminated; polydimethylsiloxane)
Japan - ENCS	N (nitrogen)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	N (nitrogen)
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
calcium carbonate	1317-65-3, 13397-26-7, 146358-95-4, 15634-14-7, 198352-33-9, 459411-10-0, 471-34-1, 63660-97-9, 72608-12-9, 878759-26-3
dimethylsiloxane, hydroxy-terminated	63148-60-7, 70131-67-8

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.