

Permatex The Right Stuff Gasket Maker PowerBead Can

ITW AAMTech

Chemwatch Hazard Alert Code: 2

Chemwatch: 6594-08

Issue Date: 08/09/2014

Version No: 6.1.1.1

Print Date: 22/09/2015

Material Safety Data Sheet according to NOHSC and ADG requirements

Initial Date: Not Available

S.Local.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Permatex The Right Stuff Gasket Maker PowerBead Can
Synonyms	PX85224
Proper shipping name	AEROSOLS
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Application is by spray atomisation from a hand held aerosol pack Elastomeric rubber.
--------------------------	--

Details of the supplier of the safety data sheet

Registered company name	ITW AAMTech	ITW AAMTech
Address	Unit 2/38 Trugood Drive, East Tamaki, Auckland 2013 New Zealand	1-9 Nina Link, Dandenong South 3175 VIC Australia
Telephone	+800 438 996	1800 177 989
Fax	+64 9272 1949	1800 308 556
Website	www.aamtech.co.nz	www.aamtech.com.au
Email	info@aamtech.co.nz	info@aamtech.com.au

Emergency telephone number

Association / Organisation	Not Available	Not Available
Emergency telephone numbers	+800 2436 2255	1800 039 008
Other emergency telephone numbers	Not Available	+61 3 9573 3112

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

Poisons Schedule	Not Applicable	
Risk Phrases ^[1]	R36/37/38	Irritating to eyes, respiratory system and skin.
	R44	Risk of explosion if heated under confinement.
	R10	Flammable.
	R48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI	
GHS Classification ^[1]	Flammable Liquid Category 3, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, STOT - SE (Resp. Irr.) Category 3, STOT - RE Category 2	

Permatex The Right Stuff Gasket Maker PowerBead Can

Legend:

1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI

Label elements

GHS label elements	  
--------------------	---

SIGNAL WORD

WARNING

Hazard statement(s)

H226	Flammable liquid and vapour
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure
AUH044	Risk of explosion if heated under confinement

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P240	Ground/bond container and receiving equipment.

Precautionary statement(s) Response

P362	Take off contaminated clothing.
P370+P378	In case of fire: Use alcohol resistant foam or fine spray/water fog for extinction.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
------	---

Label elements



Relevant risk statements are found in section 2

Indication(s) of danger

Xn

SAFETY ADVICE

S02	Keep out of reach of children.
S15	Keep away from heat.
S23	Do not breathe gas/fumes/vapour/spray.
S26	In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S281	After contact with skin, wash immediately with detergent and plenty of water.

Continued...

Permatex The Right Stuff Gasket Maker PowerBead Can

S35	This material and its container must be disposed of in a safe way.
S36	Wear suitable protective clothing.
S37	Wear suitable gloves.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S38	In case of insufficient ventilation, wear suitable respiratory equipment.
S39	Wear eye/face protection.
S40	To clean the floor and all objects contaminated by this material, use water and detergent.
S43	In case of fire use the extinguishing media detailed in section 5 of this SDS.
S45	In case of accident or if you feel unwell IMMEDIATELY contact Doctor or Poisons Information Centre (show label if possible).
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well ventilated areas.
S52	Not recommended for interior use on large surface areas.
S56	Dispose of this material and its container at hazardous or special waste collection point.
S64	If swallowed, rinse mouth with water (only if the person is conscious).

Other hazards

	Possible respiratory and skin sensitizer*.
	Limited evidence of a carcinogenic effect*.
	Cumulative effects may result following exposure*.
	Inhalation may produce health damage*.
	Vapours potentially cause drowsiness and dizziness*.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
471-34-1	25-50	<u>calcium carbonate</u>
70131-67-8	20-40	<u>dimethylsiloxane, hydroxy-terminated</u>
63148-62-9	5-20	<u>polydimethylsiloxane</u>
2224-33-1	<5	<u>vinyltris(methylethylketoxime)silane</u>
57-11-4	<3	<u>stearic acid</u>
7727-37-9.	<2	<u>nitrogen</u>
Not Available	NotSpec.	will react with moisture during curing to produce
96-29-7	0.5-2	<u>methyl ethyl ketoxime</u>

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If solids or aerosol mists are deposited upon the skin:</p> <ul style="list-style-type: none"> ▶ Flush skin and hair with running water (and soap if available). ▶ Remove any adhering solids with industrial skin cleansing cream. ▶ DO NOT use solvents. ▶ Seek medical attention in the event of irritation.

Continued...

Permatex The Right Stuff Gasket Maker PowerBead Can

Inhalation	<p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> ▶ Remove to fresh air. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor.
Ingestion	<p>Not considered a normal route of entry.</p> <ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES**Extinguishing media**

	<p>SMALL FIRE:</p> <ul style="list-style-type: none"> ▶ Water spray, dry chemical or CO2 <p>LARGE FIRE:</p> <ul style="list-style-type: none"> ▶ Water spray or fog.
--	--

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves. ▶ Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered to be a significant fire risk. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers. ▶ Aerosol cans may explode on exposure to naked flames.

SECTION 6 ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Minor Spills	<p>Slippery when spilt.</p> <ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Wear protective clothing, impervious gloves and safety glasses.
Major Spills	<p>Slippery when spilt.</p> <ul style="list-style-type: none"> ▶ Remove leaking cylinders to a safe place. ▶ Fit vent pipes. Release pressure under safe, controlled conditions ▶ Burn issuing gas at vent pipes.
	<p>Personal Protective Equipment advice is contained in Section 8 of the SDS.</p>

SECTION 7 HANDLING AND STORAGE**Precautions for safe handling**

Safe handling	<ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps.
Other information	<ul style="list-style-type: none"> ▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Aerosol dispenser.
---------------------------	--

Continued...

Permatex The Right Stuff Gasket Maker PowerBead Can

	<ul style="list-style-type: none"> Check that containers are clearly labelled.
Storage incompatibility	<ul style="list-style-type: none"> Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA






Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	calcium carbonate	Calcium carbonate (a)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	stearic acid	Stearates (a) (d)	10 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	nitrogen	Nitrogen	Not Available	Not Available	Not Available	Asphyxiant

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
calcium carbonate	Limestone; (Calcium carbonate; Dolomite)	27 mg/m3	27 mg/m3	1300 mg/m3
calcium carbonate	Carbonic acid, calcium salt	45 mg/m3	210 mg/m3	1300 mg/m3
dimethylsiloxane, hydroxy-terminated	Dimethyl(polysiloxane); (Polydimethylsiloxane, silanol terminated; Dimethylsiloxane, poly, hydroxy end-blocked)	190 mg/m3	2100 mg/m3	13000 mg/m3
polydimethylsiloxane	Dimethyl siloxane; (Dimethylpolysiloxane; Syltherm XLT; Syltherm 800; Silicone 360)	1.5 mg/m3	16 mg/m3	990 mg/m3
stearic acid	Octadecanoic acid, n-; (Stearic acid)	0.13 mg/m3	1.4 mg/m3	8.5 mg/m3
nitrogen	Nitrogen	7.96E+05 ppm	832000 ppm	869000 ppm
methyl ethyl ketoxime	Butanone oxime; (Ethyl methyl ketoxime)	10 ppm	10 ppm	52 ppm

Ingredient	Original IDLH	Revised IDLH
calcium carbonate	Not Available	Not Available
dimethylsiloxane, hydroxy-terminated	Not Available	Not Available
polydimethylsiloxane	Not Available	Not Available
vinyltris(methylethylketoxime)silane	Not Available	Not Available
stearic acid	Not Available	Not Available
nitrogen	Not Available	Not Available
will react with moisture during curing to produce	Not Available	Not Available
methyl ethyl ketoxime	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.</p>
Personal protection	    

Permatex The Right Stuff Gasket Maker PowerBead Can

Eye and face protection	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▶ No special equipment needed when handling small quantities. ▶ OTHERWISE: ▶ For potentially moderate exposures: ▶ Wear general protective gloves, eg. light weight rubber gloves. ▶ For potentially heavy exposures: ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.
Body protection	See Other protection below
Other protection	No special equipment needed when handling small quantities. OTHERWISE: <ul style="list-style-type: none"> ▶ Overalls. ▶ Skin cleansing cream. ▶ Eyewash unit.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Permatex The Right Stuff Gasket Maker PowerBead Can Not Available

Material	CPI
----------	-----

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS P2	-	A-PAPR-AUS / Class 1 P2
up to 50 x ES	-	A-AUS / Class 1 P2	-
up to 100 x ES	-	A-2 P2	A-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Black paste with a mild odour; not miscible with water. Will react with moisture during curing to release methylethyl ketoxime.		
Physical state	Non Slump Paste	Relative density (Water = 1)	1.34
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7-8	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	>93 (TCC)	Taste	Not Available

Continued...

Permatex The Right Stuff Gasket Maker PowerBead Can

Evaporation rate	<1 BuAC = 1	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	<3% (VOC - by wt)
Vapour pressure (kPa)	<0.67	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	3.0	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▸ Elevated temperatures. ▸ Presence of open flame. ▸ Product is considered stable. ▸ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	<p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas.</p>
Ingestion	<p>Not normally a hazard due to physical form of product.</p> <p>Considered an unlikely route of entry in commercial/industrial environments</p> <p>Silicone fluids do not have a high acute toxicity. They may have a laxative effect and produce central nervous system depression.</p>
Skin Contact	<p>There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Excessive use or prolonged contact may lead to defatting, drying and irritation of sensitive skin</p>
Eye	<p>This material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.</p> <p>Eye exposure to silicone fluids causes temporary irritation of the conjunctiva. Injection into the specific structures of the eye, however, causes corneal scarring, permanent eye damage, allergic reactions and cataract, and may lead to blindness.</p>
Chronic	<p>There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.</p>

Permatex The Right Stuff Gasket Maker PowerBead Can	TOXICITY	IRRITATION
	Not Available	Not Available
calcium carbonate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 0.75 mg/24h - SEVERE

Continued...

Permatex The Right Stuff Gasket Maker PowerBead Can

	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-moderate
	Oral (rat) LD50: 6450 mg/kg ^[2]	
dimethylsiloxane, hydroxy-terminated	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >15520 mg/kg ^[2]	Nil reported
	Inhalation (rat) LC50: >8.75 mg/L/7H ^[2]	
	Oral (rat) LD50: >5000 mg/kg*d ^[2]	
	Oral (rat) LD50: >62080 mg/kg ^[2]	
polydimethylsiloxane	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye (rabbit): 100 mg/1h - mild
	Oral (rat) LD50: >17000 mg/kg ^[2]	
vinyltris(methylethylketoxime)silane	TOXICITY	IRRITATION
	Not Available	Not Available
stearic acid	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Skin (human): 75 mg/3d-I-mild
	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-moderate
nitrogen	TOXICITY	IRRITATION
	Not Available	Not Available
methyl ethyl ketoxime	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >184<2 mg/kg ^[1]	Eye (rabbit): 0.1 ml - SEVERE
	Inhalation (rat) LC50: 20 mg/l/4h ** ^[2]	
	Oral (rat) LD50: >900 mg/kg ^[1]	

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

CALCIUM CARBONATE	No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic effects.
DIMETHYLSILOXANE, HYDROXY-TERMINATED	Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility. * [Mobay Chemical Corp] **[GE]
POLYDIMETHYLSILOXANE	Siloxanes may impair liver and hormonal function, as well as the lung and kidney. They have not been found to be irritating to the skin and eyes. They may potentially cause cancer (tumours of the womb in females) and may cause impaired fertility or infertility. The material may be irritating to the eye, with prolonged contact causing inflammation. No toxic response noted during 90 day subchronic inhalation toxicity studies The no observable effect level is 450 mg/m3. Non-irritating and non-sensitising in human patch test. [Xerox]*
STEARIC ACID	Equivocal tumorigen by RTEC criteria
NITROGEN	No significant acute toxicological data identified in literature search.
METHYL ETHYL KETOXIME	Mammalian lymphocyte mutagen *Huls Canada ** Merck
Permatex The Right Stuff Gasket Maker PowerBead Can & VINYLTRIS(METHYLETHYLKETOXIME)SILANE & METHYL ETHYL KETOXIME	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.
CALCIUM CARBONATE & STEARIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material

Continued...

Permatex The Right Stuff Gasket Maker PowerBead Can

ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.

Acute Toxicity	⊘	Carcinogenicity	⊘
Skin Irritation/Corrosion	✓	Reproductivity	⊘
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	⊘	STOT - Repeated Exposure	✓
Mutagenicity	⊘	Aspiration Hazard	⊘

Legend: ✓ – Data required to make classification available
 ✗ – Data available but does not fill the criteria for classification
 ⊘ – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
stearic acid	LOW	LOW
methyl ethyl ketoxime	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
stearic acid	LOW (LogKOW = 8.23)
methyl ethyl ketoxime	LOW (BCF = 6)

Mobility in soil

Ingredient	Mobility
stearic acid	LOW (KOC = 11670)
methyl ethyl ketoxime	LOW (KOC = 130.8)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Consult State Land Waste Management Authority for disposal. ▶ Discharge contents of damaged aerosol cans at an approved site. ▶ Allow small quantities to evaporate. ▶ DO NOT incinerate or puncture aerosol cans.
------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO
HAZCHEM	2YE

Permatex The Right Stuff Gasket Maker PowerBead Can

Land transport (ADG)

UN number	1950
Packing group	Not Applicable
UN proper shipping name	AEROSOLS
Environmental hazard	No relevant data
Transport hazard class(es)	Class : 2.2 Subrisk : Not Applicable
Special precautions for user	Special provisions : 63 190 277 327 344 Limited quantity : See SP 277

Air transport (ICAO-IATA / DGR)

UN number	1950
Packing group	Not Applicable
UN proper shipping name	Aerosols, non-flammable (containing biological products or a medicinal preparation which will be deteriorated by a heat test); Aerosols, non-flammable
Environmental hazard	No relevant data
Transport hazard class(es)	ICAO/IATA Class : 2.2 ICAO / IATA Subrisk : Not Applicable ERG Code : 2L
Special precautions for user	Special provisions : A98A145A167A802 Cargo Only Packing Instructions : 204; 203 Cargo Only Maximum Qty / Pack : 150 kg Passenger and Cargo Packing Instructions : 204; 203 Passenger and Cargo Maximum Qty / Pack : 75 kg Passenger and Cargo Limited Quantity Packing Instructions : Y204; Y203 Passenger and Cargo Limited Maximum Qty / Pack : 30 kg G

Sea transport (IMDG-Code / GGVSee)

UN number	1950
Packing group	Not Applicable
UN proper shipping name	AEROSOLS
Environmental hazard	Not Applicable
Transport hazard class(es)	IMDG Class : 2.2 IMDG Subrisk : Not Applicable
Special precautions for user	EMS Number : F-D , S-U Special provisions : 63 190 277 327 344 959 Limited Quantities : See SP277

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	polydimethylsiloxane	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	stearic acid	Y

Continued...

Permatex The Right Stuff Gasket Maker PowerBead Can

IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	methyl ethyl ketoxime	Y
---	-----------------------	---

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

CALCIUM CARBONATE(471-34-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

DIMETHYLSILOXANE, HYDROXY-TERMINATED(70131-67-8) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

POLYDIMETHYLSILOXANE(63148-62-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

VINYLTRIS(METHYLETHYLKETOXIME)SILANE(2224-33-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

STEARIC ACID(57-11-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

NITROGEN(7727-37-9.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Inventory of Chemical Substances (AICS)

METHYL ETHYL KETOXIME(96-29-7) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Substances Information System - Consolidated Lists

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (methyl ethyl ketoxime; dimethylsiloxane, hydroxy-terminated; nitrogen; polydimethylsiloxane; vinyltris(methylethylketoxime)silane; stearic acid)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	N (dimethylsiloxane, hydroxy-terminated; polydimethylsiloxane)
Japan - ENCS	N (nitrogen)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	N (nitrogen)
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
calcium carbonate	1317-65-3, 13397-26-7, 146358-95-4, 15634-14-7, 198352-33-9, 459411-10-0, 471-34-1, 63660-97-9, 72608-12-9, 878759-26-3
dimethylsiloxane, hydroxy-terminated	63148-60-7, 70131-67-8

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

Continued...

Permatex The Right Stuff Gasket Maker PowerBead Can

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.