

# WYNN'S DIESEL INJECT-A-CLEAN

Chemwatch Material Safety Data Sheet  
Issue Date: 21-Dec-2012  
9317SP

Hazard Alert Code: MODERATE

CHEMWATCH 27-1523  
Version No:3.1.1.1  
Page 1 of 7

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

WYNN'S DIESEL INJECT-A-CLEAN

### PRODUCT USE

Cleaning fluid for diesel engine fuel systems.

### SUPPLIER

Company: ITW AAMTech  
Address:  
100 Hassall Street  
Wetherill Park  
NSW, 2164  
Australia  
Telephone: +61 2 9828 0900  
Emergency Tel: **1800 039 008 (24 hours)**  
Emergency Tel: **+61 3 9573 3112 (24 hours)**  
Fax: +61 2 9725 4698

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS.** According to the Criteria of NOHSC, and the ADG Code.

COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

### RISK

Risk Codes	Risk Phrases
R40(3)	• Limited evidence of a carcinogenic effect.
R65	• HARMFUL- May cause lung damage if swallowed.
R67	• Vapours may cause drowsiness and dizziness.

### SAFETY

Safety Codes	Safety Phrases
S23	• Do not breathe gas/fumes/vapour/spray.
S24	• Avoid contact with skin.
S36	• Wear suitable protective clothing.
S37	• Wear suitable gloves.
S401	• To clean the floor and all objects contaminated by this material, use water and detergent.
S13	• Keep away from food, drink and animal feeding stuffs.
S46	• If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
middle distillate	68476-34-6	>60
naphtha petroleum, light aromatic solvent	64742-95-6.	<10
other non- hazardous ingredients		<10

continued...

# WYNN'S DIESEL INJECT-A-CLEAN

Chemwatch Material Safety Data Sheet  
Issue Date: 21-Dec-2012  
9317SP

Hazard Alert Code: MODERATE

CHEMWATCH 27-1523  
Version No:3.1.1.1  
Page 2 of 7

## Section 4 - FIRST AID MEASURES

### SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

### EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

### SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

### NOTES TO PHYSICIAN

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO<sub>2</sub> 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

## Section 5 - FIRE FIGHTING MEASURES

### EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.

### FIRE/EXPLOSION HAZARD

- Combustible.
  - Slight fire hazard when exposed to heat or flame.
  - Heating may cause expansion or decomposition leading to violent rupture of containers.
  - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include: carbon dioxide (CO<sub>2</sub>), other pyrolysis products typical of burning organic material.

continued...

# WYNN'S DIESEL INJECT-A-CLEAN

Chemwatch Material Safety Data Sheet  
Issue Date: 21-Dec-2012  
9317SP

Hazard Alert Code: MODERATE

CHEMWATCH 27-1523

Version No:3.1.1.1

Page 3 of 7

Section 5 - FIRE FIGHTING MEASURES

## FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## HAZCHEM

None

## Section 6 - ACCIDENTAL RELEASE MEASURES

### MINOR SPILLS

Slippery when spilt.

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

### MAJOR SPILLS

Slippery when spilt.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/sec until fill pipe submerged to twice its diameter, then  $\leq 7$  m/sec).
- Avoid splash filling.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

### SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

Avoid storage with oxidisers.

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.

continued...

# WYNN'S DIESEL INJECT-A-CLEAN

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet  
Issue Date: 21-Dec-2012  
9317SP

CHEMWATCH 27-1523  
Version No:3.1.1.1  
Page 4 of 7

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC	Notes
Australia Exposure Standards	naphtha petroleum, light aromatic solvent (Petrol (gasoline))		900						(see Chapter 16)

The following materials had no OELs on our records

- middle distillate: CAS:68476- 34- 6 CAS:68334- 30- 5

### MATERIAL DATA

MIDDLE DISTILLATE:

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

WYNN'S DIESEL INJECT-A-CLEAN:

None assigned. Refer to individual constituents.

MIDDLE DISTILLATE:

CAUTION: This substance has been proposed by the ACGIH as A3 Animal Carcinogen (at relatively high doses).

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

TLV TWA: 100 mg/m<sup>3</sup> as total hydrocarbons, vapour and aerosol Skin A3

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT:

Odour threshold: 0.25 ppm.

The TLV-TWA is protective against ocular and upper respiratory tract irritation and is recommended for bulk handling of gasoline based on calculations of hydrocarbon content of gasoline vapour.

REL TWA: 25-100 ppm\*, 125 mg/m<sup>3</sup>\* [Various Manufacturers]

CEL TWA: 50 ppm, 125 mg/m<sup>3</sup>

### PERSONAL PROTECTION

#### RESPIRATOR

- Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

#### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

#### HANDS/FEET

- Neoprene gloves.
- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.

#### OTHER

- Overalls.
- P.V.C. apron.

continued...

# WYNN'S DIESEL INJECT-A-CLEAN

Chemwatch Material Safety Data Sheet  
Issue Date: 21-Dec-2012  
9317SP

Hazard Alert Code: MODERATE

CHEMWATCH 27-1523  
Version No:3.1.1.1  
Page 5 of 7

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Barrier cream.
- Skin cleansing cream.

### ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Clear thin amber liquid with petroleum distillate odour; does not mix with water.

### PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Applicable	Viscosity	Not Available
Boiling Range (°C)	>207	Solubility in water (g/L)	Immiscible
Flash Point (°C)	64 (PMCC)	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.837@15C
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

## Section 10 - STABILITY AND REACTIVITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.
- Presence of heat source and ignition source.

*For incompatible materials - refer to Section 7 - Handling and Storage.*

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

■ Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

##### EYE

■ There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

##### SKIN

■ Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

continued...

WYNN'S DIESEL INJECT-A-CLEAN

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet  
Issue Date: 21-Dec-2012  
9317SP

CHEMWATCH 27-1523  
Version No:3.1.1.1  
Page 6 of 7

Section 11 - TOXICOLOGICAL INFORMATION

INHALED

■ Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.  
There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.  
Inhalation hazard is increased at higher temperatures.  
Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.

CHRONIC HEALTH EFFECTS

■ There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

No data

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
middle distillate	No Data Available	No Data Available	No Data Available	No Data Available
naphtha petroleum, light aromatic solvent	No Data Available	No Data Available	No Data Available	No Data Available

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

Indications of Danger:

Xn Harmful

continued...

# WYNN'S DIESEL INJECT-A-CLEAN

## Chemwatch Material Safety Data Sheet

Issue Date: 21-Dec-2012

9317SP

Hazard Alert Code: MODERATE

CHEMWATCH 27-1523

Version No:3.1.1.1

Page 7 of 7

Section 15 - REGULATORY INFORMATION

## POISONS SCHEDULE

S5

## REGULATIONS

### Regulations for ingredients

**middle distillate (CAS: 68476-34-6, 68334-30-5) is found on the following regulatory lists;**

"Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "OSPAR National List of Candidates for Substitution – Norway", "OSPAR National List of Candidates for Substitution – United Kingdom", "Verzenden Namen"

**naphtha petroleum, light aromatic solvent (CAS: 64742-95-6) is found on the following**

**regulatory lists;**

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "OSPAR National List of Candidates for Substitution – Norway"

**No data for Wynn's Diesel Inject-A-Clean (CW: 27-1523)**

## Section 16 - OTHER INFORMATION

### INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
middle distillate	68476-34-6, 68334-30-5

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 21-Dec-2012

Print Date: 23-Jan-2013

*This is the end of the MSDS.*