Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2012

9317SP

CHEMWATCH 4847-75 Version No:2.1.1.1 CD 2012/3 Page 1 of 7

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

WYNN'S PETROL COMPLETE FUEL SYSTEM CLEANER

SYNONYMS

"Product Code: 72018"

PRODUCT USE

Petrol fuel system cleaner.

SUPPLIER

Company: ITW AAMTech Company: Wynn' s New Zealand

Address: Address:

100 Hassall Street Unit 2, 38 Trugood Drive

Wetherill Park East Tamaki
NSW, 2164 Auckland, 2013
Australia New Zealand

Telephone: +61 2 9828 0900 Telephone: +64 9272 1940

Emergency Tel: **1800 039 008 (24 hours)**Emergency Tel: **1800 039 008 (24 hours)**

Fax: +61 2 9725 4698 Fax: +64 9272 1949

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

RISK

Risk Codes Risk Phrases

R65
 HARMFUL- May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

SAFETY

Safety Codes Safety Phrases

• Wear suitable protective clothing.

• Wear suitable gloves.

To clean the floor and all objects contaminated by this material, use water

and detergent.

• Keep away from food, drink and animal feeding stuffs.

If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show

this container or label).

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME CAS RN % fuel oil, No. 2 None >60 naphtha petroleum, light aromatic solvent 64742-95-6 <10 other non- hazardous ingredients <10

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and

Chemwatch Independent Material Safety Data Sheet Issue Date: 7-Aug-2012 9317SP

CHEMWATCH 4847-75 Version No:2.1.1.1 CD 2012/3 Page 2 of 7 Section 4 - FIRST AID MEASURES

prevent aspiration.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:
- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- · Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.

FIRE/EXPLOSION HAZARD

- · Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon dioxide (CO2), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

 Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

None

Chemwatch Independent Material Safety Data Sheet Issue Date: 7-Aug-2012 9317SP

CHEMWATCH 4847-75 Version No:2.1.1.1 CD 2012/3 Page 3 of 7

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Slippery when spilt.
- · Remove all ignition sources.
- · Clean up all spills immediately.
- · Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

MAJOR SPILLS

■ Slippery when spilt.

Moderate hazard.

- Clear area of personnel and move upwind.
- · Alert Fire Brigade and tell them location and nature of hazard.
- · Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- · Metal can or drum
- · Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid storage with oxidisers.

STORAGE REQUIREMENTS

- · Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS Source Material TWA mg/m³ Notes Australia Exposure Standards Wynn's Petrol Complete Fuel System Cleaner (Petrol 900 (see Chapter 16)

(gasoline))

MATERIAL DATA

FUEL OIL, NO. 2:

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT:

■ Odour threshold: 0.25 ppm.

The TLV-TWA is protective against ocular and upper respiratory tract irritation and is recommended for bulk handling of gasoline based on calculations of hydrocarbon content of gasoline vapour.

FUEL OIL, NO. 2:

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

WYNN'S PETROL COMPLETE FUEL SYSTEM CLEANER:

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2012 9317SP

CHEMWATCH 4847-75 Version No:2.1.1.1 CD 2012/3 Page 4 of 7

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

■ None assigned. Refer to individual constituents.

FUEL OIL, NO. 2:

■ CAUTION: This substance has been classified by the ACGIH as A3 Animal Carcinogen (at relatively high doses). Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

CAUTION: This substance is classified by the NOHSC as Category 3 Suspected of having carcinogenic potential.

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT:

■ WARNING: This substance is classified by the NOHSC as Category 2 Probable Human Carcinogen.

REL TWA: 25-100 ppm*, 125 mg/m3* [Various Manufacturers]

CEL TWA: 50 ppm, 125 mg/m3

PERSONAL PROTECTION

RESPIRATOR

•Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- · Safety glasses with side shields.
- · Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear chemical protective gloves, eq. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- · Skin cleansing cream.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear thin amber liquid with a petroleum distillate odour; does not mix with water.

PHYSICAL PROPERTIES

Does not mix with water.

Floats on water.

State Liquid Molecular Weight Not Applicable Not Available Melting Range (℃) Not Applicable Viscosity Boiling Range (℃) Solubility in water (g/L) >207 Immiscibl e Flash Point (℃) 64 (PMCC) pH (1% solution) Not Applicable Decomposition Temp (℃) Not Available pH (as supplied) Not A pplicable Autoignition Temp (℃) Not Available Vapour Pressure (kPa) Not Available Upper Explosive Limit (%) Not Available Specific Gravity (water=1) 0.837 @ 15 C

Chemwatch Independent Material Safety Data Sheet

Issue Date: 7-Aug-2012 9317SP CHEMWATCH 4847-75 Version No:2.1.1.1 CD 2012/3 Page 5 of 7

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Lower Explosive Limit (%) Not Available Relative Vapour Density >

(air=1)

Volatile Component (%vol) Not Available Evaporation Rate Not Available

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- · Product is considered stable.
- · Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

FYF

■ There is some evidence to suggest that this material can cause eye irritation and damage in some persons.

JKIIV

■ There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

INHALED

■ Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

Inhalation hazard is increased at higher temperatures.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

CHRONIC HEALTH EFFECTS

■ Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

TOXICITY AND IRRITATION

■ Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

No data

Ecotoxicity

Ingredient Persistence: Persistence: Air Bioaccumulation
Water/Soil

fuel oil, No. 2

No Data
Available

naphtha petroleum, light
aromatic solvent

No Data
Available

No Data

No Data

Available

Available

Mobility

Chemwatch Independent Material Safety Data Sheet Issue Date: 7-Aug-2012 9317SP

CHEMWATCH 4847-75 Version No:2.1.1.1 CD 2012/3 Page 6 of 7

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: COMBUSTIBLE LIQUID, regulated under AS1940 for Bulk Storage purposes only.

HAZCHEM: None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

POISONS SCHEDULE S5

REGULATIONS

Regulations for ingredients

fuel oil, No. 2 (CAS: 68476-30-2) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)",
"Australia Inventory of Chemical Substances (AICS)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5",
"GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Fragrance Association (IFRA) Survey: Transparency List", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway"

naphtha petroleum, light aromatic solvent (CAS: 64742-95-6) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)",
"Australia Inventory of Chemical Substances (AICS)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5",
"GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "International Maritime Dangerous Goods Requirements (IMDG Code) - Substance Index", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "OSPAR National List of Candidates for Substitution – Norway"

No data for Wynn's Petrol Complete Fuel System Cleaner (CW: 4847-75)

Section 16 - OTHER INFORMATION

- Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

 A list of reference resources used to assist the committee may be found at: www.chemwatch.net/references.
- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 7-Aug-2012 Print Date: 7-Aug-2012

Chemwatch Independent Material Safety Data Sheet Issue Date: 7-Aug-2012 9317SP

CHEMWATCH 4847-75 Version No:2.1.1.1 CD 2012/3 Page 7 of 7 Section 16 - OTHER INFORMATION

This is the end of the MSDS.